

District I
PO Box 1980, Hobbs, NM 88241-1980
District II
PO Drawer DD, Artesia, NM 88211-0719
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

Form C-101
Revised February 10, 1994
Instructions on back
Submit to Appropriate District Office
State Lease - 6 Copies
Fee Lease - 5 Copies

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

Operator Name and Address: AMERADA HESS CORPORATION P.O. BOX 2040 HOUSTON, TEXAS 77252		ATTN: ONSHORE DRILLING SERVICES	¹ OGRID Number 000495
			² API Number 30-025-33045
³ Property Code 000134	⁴ Property Name MONUMENT ABO UNIT		⁵ Well No. 2

⁷ Surface Location

UL or lot no.	Section	Township	Range	Lot Ida	Feet from the	North/South line	Feet from the	East/West line	County
M	35	19S	36E		660	SOUTH	330	WEST	LEA

⁸ Proposed Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Ida	Feet from the	North/South line	Feet from the	East/West line	County
⁹ Proposed Pool 1 MONUMENT/ABO					¹⁰ Proposed Pool 2 46970				

¹¹ Work Type Code N	¹² Well Type Code Q	¹³ Cable/Rotary R	¹⁴ Lease Type Code P	¹⁵ Ground Level Elevation 3612'
¹⁶ Multiple NO	¹⁷ Proposed Depth 8000'	¹⁸ Formation ABO	¹⁹ Contractor UNKNOWN	²⁰ Spud Date AUGUST 1, 1995

²¹ Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/feet	Setting Depth	Sacks of Cement	Estimated TOC
14-3/4"	11-3/4"	47#	400'	400	SURFACE
11"	8-5/8"	24#	4600'	2200	-11-
7-7/8"	5-1/2"	15.5#	8000'	700	-11-

²² Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

DRILL 14-3/4" HOLE TO 400' AND SET 400' OF 47# 11-3/4" SURFACE CASING. CEMENT W/400 SX AND CIRCULATE TO SURFACE.

DRILL 11" HOLE TO 4600' AND SET 4600' OF 24# 8-5/8" INTERMEDIATE CASING. CEMENT W/2200 SX AND CIRCULATE TO SURFACE.

DRILL 7-7/8" HOLE TO 8000' AND SET 8000' OF 15.50# 5-1/2" PRODUCTION CASING. CEMENT W/700 SX TO SURFACE.

²³ I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature

Printed name:

MIKE JUMPER

Title:

ADM. SUPERVISOR DRILLING SERVICES

Date:

07-20-95

Phone:

713-609-4846

OIL CONSERVATION DIVISION

Approved by:

Orig. Signed by
Paul Kautz

Title:

Geologist

Approval Date:

AUG 02 1995

Expiration Date:

Conditions of Approval:

Attached ☐

RECEIVED

AUG 18 1990

**OLD HOBBS
OFFICE**