	N.M. Oil Cons. Vision			
Form 3160-5 (June 1990)	DEPARTME	1625 N. French Dr. ITED STATES Hobbs, NM 88240 NT OF THE INTERIOR LAND MANAGEMENT	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No.	
Do not use this fo	LC-065607 6. If Indian, Allottee or Tribe Name			
SUBMIT IN TRIPLICATE			7. If Unit or CA, Agreement Designation	
X Oil Weil Gas Other 2 Name of Operator Read & Stevens, Inc. 3 Address and Telephone No. P. O. Box 1518 Roswell, New Mexico 88202 505/622-3770 4 Location of Well (Footage, Sec., T., R., M., or Survey Description) 1650' FNL & 2310' FWL Section 4 T20S-R34E 12 CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOF			 8. Well Name and No. <u>Hudson Federal #4</u> 9. API Well No. <u>30-025-33181</u> 10. Field and Pool, or Exploratory Area <u>NE Lea Delaware</u> 11. County or Parish, State Lea County, New Mexico BL OB OTHER DATA 	
TYPE OF SUBMISSION		TYPE OF ACTION		
X Notice of Subsequen		Abandonment Recompletion Plugging Back Casing Repair Altering Casing X Other Plug & Abandon	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

07/18/00 Read & Stevens proposes to plug and abandon the subject well. A cast iron bridge plug was previously set @ 8,025' with 25' of cement on top. Also, a CIBP was previously set @ 7,225'. Read & Stevens proposes to dump bail cement on top of the CIBP @ 7,225'. The Cherry Canyon perforations from 5,600' to 5,620' will then be abandoned by setting a CIBP w/ 35' cmt on top @ 5,500' at the top of the Delaware. A 140' cement plug will be set @ the top of the Seven Rivers from 3,910' to 3,770'. The 5 ¹/₂" casing will then be cut and pulled from 3,700'. A 100' cement plug will be set at the top of the salt from 1,550' to 1,650', a 100' cement plug from 500' to 400', and a 50' surface plug. The dry hole marker will be set and location cleaned up.

14 I hereby certify that the foregoing is true and correct Signed Title <u>Operations Manager</u> 7-18-00 Date (This space for Federal or State office use) (ORIG. SGD.) GARY GOURLEY PETROLEUM ENGINEER **78**80 Title Date ns of approval, if any itle 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

nin



