

1625 N. French Dr., Hobbs, NM 88240

811 South First, Artesia, NM 88210

1000 Rio Brazos Rd., Aztec, NM 87410

1220 S. St. Francis Dr., Santa Fe, NM 87504

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87504

WELL API NO.

30-025-33199

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil &amp; Gas Lease No.

17978

7. Lease Name or Unit Agreement Name:

E.H. Caddis

7. Well No.

#1

9. Pool name or Wildcat

Monument (Abo)

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other Dry Hole

2. Name of Operator

David H. Arrington Oil &amp; Gas

3. Address of Operator

P.O. Box 2071 Midland, Texas

4. Well Location

Unit Letter L : 1650 feet from the South line and 330 feet from the West lineSection 2 Township 20S Range 36E NMPM County Lea Co.

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

## 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐OTHER: ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒CASING TEST AND CEMENT JOB ☐OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

6/3/96 - Circulate hole with 9.5# mud from 7500' to surface;

6/4/96 - Set 4 1/2" CIBP at 7090'. Run dump bailer and cap with 40' of cement;

6/6/96 - Jet cut 4 1/2" "c" cement at 5007'. Laydown casing;

6/6/96 - Spot 35 sacks "c" cement at 5050'. WOC;

6/7/96 - Tag TOC at 4988'. Spot 25 sacks "c" cement at 4980'. Top of plug about 4953';

6/7/96 - Spot 60 sacks "c" 3990', WOC. Tag TOC at 3854';

6/7/96 - Spot 70 sacks "c" cement at 3160'. WOC;

6/10/96 - Tag TOC at 2985'. Tested casing to 500 psi and held;

6/10/96 - Spot 35 sacks "c" cement at 1287'. Top of plug at 1172';

6/10/96 - Spot 10 sacks "c" cement at 33'. BGL to surface;

6/11/96 - Cut off wellhead 4' BGL and install dry hole marker.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Chuck Sledge TITLE Operations Engineer DATE 2/5/01Type or print name Chuck Sledge

Telephone No. (915) 682-6685

(This space for State use)

APPROVED BY Johnny Robinson TITLE CHIEF DATE 2/5/01

Conditions of approval, if any: