BUREAU OF SUNDRY NOTICES A Do not use this form for proposals to dri	TED STATES NT OF THE INTERIOR LAND MANAGEMENT ND REPORTS ON WELLS Il or to deepen or reentry to a dir R PERMIT - " for such proposals		S. COMMILIE BOREXI Budget Burea 1 No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No. NM - 1150 6. If Indian, Allotte: or Tribe Name	
SUBMI	T IN TRIPLICATE		7. If Unit or CA, Agreement Designat	tion
<ol> <li>Type of Well X Oil Well Gas Well Other         Other         Other</li></ol>	Description)	4	<ul> <li>8. Well Name and No.</li> <li>Reed A-3 Federal</li> <li>9. API Well No.</li> <li>30-025-33300</li> <li>10. Field and Pool, or exploratory Area</li> <li>Monument Abo</li> <li>11. County or Parish, State</li> </ul>	# 16
12. CHECK APPROPRIATE BOX(	s) TO INDICATE NATURE OF	NOTICE, REPORT,		<u>M.</u>
TYPE OF SUBMISSION		TYPE OF ACTION		
Notice of Intent	Abandonment	· · ·	Change of Plars	
Subsequent Report	Recompletion Plugging Back		New Construction	
Final Abandonment Notice	Casing Repair Altering Casing X Other New	Well Completion.	Water Shut-Off     Conversion to Injection     Dispose Water     (Note: Report results of multiple completion)	877 VI
<ul> <li>B. Describe Proposed or Completed Operations (Clearly state give subsurface locations and measured and true v</li> <li>5-9 thru 6-12-96: Swabbed &amp; flowed well. 5-20-96: N</li> <li>w/tbg. &amp; pkr. TIH w/TAC on 2-7/8' installed wellhead. TIH w/20-125-motor. Connected electrical svc. 214 b.w. and OMCFG. 5/29/96=MIRU Halliburton EZ drill cement retair 7224'-7286' w/130sks. class "C" cesement retainer &amp; circ.4sks. to pi Drilled out retainer &amp; cement to 7 300 PSI in 3 min. TOH w/ bit. MIR 5-1/2" csg. w/4 SPF using hyper je 7278', &amp; fr. 7281'-7286'. Knox Sv TAC on 2-7/8" tbg. Tbg. at 7278' 20-150-RHBC-30-6-0 pump on rods. on 6/11/96. 6/12/96: Warren Petro Test of 6/18/96: Pumped 3 b.o., 27</li> <li>14. Thereby certify that the foregoing is frue and correct Signed</li></ul>	IRU Pride Well Svc., remove tbg. Set TAC at 7151' w/t RHBC-24-6H4 rod pump on rod and began pumping well on 5 Pride Well Svc. & TOH with her set at 7145'. Halliburto ement. Pumped 108 sks. into t. WOC. TIH w/4-3/4" bit. 320'. Circ. hole clean & pr U Schlumberger. Ran G/R Lo t charges fr. 7224'-7227', c. acidized perfs. w/ 1500 w/TAC at 7102'. Removed BO RDPU, cleaned location & re leum set sales meter No. 839	d wellhead, instal bg. set at 7280'. s. RDPU. Set pun /22/96. 5/28/96=p prod. egpt. TIH w/ n squeezed Abo zor perfs. & formatic Tagged cement at ess. csg & tbg. w/ g. TIH & perforat 7261'-7265', 7268' gal 15% HCL & swab P & installed well sumed pumping well 5 & began taking g urs.	Completion of Reconsiletion Report and Log ing any proposed work. If well is directional Removed BOP & mping unit and pumped 0 b.o., 75-1/2 he perfs. fr. on 18sks. below 7139'. 71000PSI. Lost ced Abo zone -7271', 7276'- bed well TIH w/ head. TIH w/ to frac tanks	· · · · ·
(This space for Federal or State office use)	D			

1

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfally to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

í