Fo-in 3160-5 (November 1994)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANA JEMENT**

N.M. Oil Cons. Division PO Boy 1000

FORM APPROVED OMB No. 1004-0135 Expires July 31, 1996

	**			r.U. bu	
UNDRY NOTICES A	ND	REPORTS	ON WE	LLSHobbs	NM 8824

SUNDRY NOTICES AND REPORTS ON WELLSHobbs, NM 88241 Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals. SUBMIT IN TRIPLICATE - Other Instructions on reverse side					NM 89873 6. If Indian, Allottee or Tribe Name 7. If Unit or CA/Agreement, Name and/or No.			
								1. Type of Well Soil Well Gas Well Cher
2. Name of Operator OXY USA INC. 16696						9. API Well No.		
Ba. Address P.O. BOX 50250 3b. Phone No. (include area code)						30-025-333-4		
MIDLAND, TX 79710-0250 915-685-5717						10. Field and Pool, or Exploratory Area Wildcut Done Springs		
Location of Well (Foolage, Sec., T., R., M., or Survey Description) 1650 FNL 1650 FWL SENW(F) SEC 21 T205 R36E						or Parish, State NM	<u> </u>	
12. CHECK APPRO	OPRIATE BOX(ES) TO) INDICAT	E NATURE	OF NOTICE, R	EPORT, OR	OTHER DAT	A	
TYPE OF SUBMISSION			TYPE (OF ACTION				
Subsequent Report	Acidize Alter Casing Casing Repair	Deepen Fracture New Con	Treat	Reclamation	/Resume)	Water Shut-O Well Integrity Other		
Final Abandonment Notice	Change Plans Convert to Injection	Plug and Plug Bac	Abandon	Temporarily Ab Water Disposal				
 Describe Proposed or Completed Op If the proposal is to deepen direction. Attach the Bond under which the we following completion of the involved testing has been completed. Final A determined that the site is ready for fi 	ork will be performed or pro- l operations. If the operation abandonment Notices shall b	vide the Bond	No. on file with	BLM/BIA. Requi	red subsequent	hs of all pertinent in reports shall be fi	markers and zones led within 30 day	
	OXY Tiger Federa TD-11100' PBTD- 13-3/8" 48# csg @ 8-5/8" 32# csg @ 5 5-1/2" 17# csg @ 1 CIBP @ 10890' w/	-10855' Po 440', cmt v 5510', cmt v 11100', cmt	w/ 420sx, 17 w/ 2275sx. 1 w/ 450sx 7	-1/2" hole, TOC-5	Surface			
	1. M&P 25sx cmt fr 2. RIH & set CIBP (3. Cut & pull 5-1/2" 4. M&P 40sx cmt fr 5. M&P 50sx cmt fr 6. M&P 45sx cmt fr 7. M&P 40sx cmt fr 8. M&P 35sx cmt fr 8. M&P 35sx cmt fr 9. Spot 10sx surfac	@ 9250', c csg @ app rom 8500-8 rom 7054-6 rom 5560-5 rom 3460-3 rom 1200-1 rom 490-39	dump 5sx (35 proximately 8 400' 954' 460' 1360' 100'	5') cmt on top 3450'				
4. I hereby certify that the foregoing is Name (Printed/Typed) DAVID S			Title	REGULATOR	V ANIAT YO	Υ.		
Signature Out To	W.		Date	12/8/9		1		
	THIS SPACE F	OR FEDER	AL OR STAT	E OFFICE USE		****		

Approved by (ORIG. SGD.) GARY GOURLEY PETROLEUM ENGINEER

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the U- ed States any false, ficultous or fraudulent statements or representations as to any matter within its jurisdiction.

OXY USA INC. PROPOSED
OXY TIGER FEDERAL #!
SEC 21 T20S R36E LEA NM

0.0 - 30.0' CEMENT PLUG 10sx 390.0 - 490.0' CEMENT PLUG 35sx 1100.0 - 1200.0' CEMENT PLUG 35sx 0.0 - 440.0' 17 1/2" OD HOLE 0.0 - 440.0' CEMENT 420sx-CIRC 0.0 - 440.0' 13 3/8" OD SURF CSG

3360.0 - 3460.0' CEMENT PLUG 40sx

440.0 - 5510.0' 11" OD HOLE 0.0 - 5510.0' CEMENT 2275sx 0.0 - 5510.0' 8 5/8" OD INT CSG

5460.0 - 5560.0' CEMENT PLUG 45sx

6954.0 - 7054.0' CEMENT PLUG 50sx

8400.0 - 8500.0' CEMENT PLUG 40sx

9215.0 - 9250.0' CEMENT PLUG 5sx 9250.0 - 9250.0' CIBP

9784.0 - 9884.0' CEMENT PLUG 25sx


10855.0 - 10890.0' CEMENT PLUG 5sx 10890.0 - 10890.0' CIBP 5510.0 - 11100.0' 7 7/8" OD HOLE 8500.0 - 11100.0' CEMENT 450sx-CBL 8450.0 - 11100.0' 5 1/2" OD PROD CSG

9300.0 - 9304.0' ABANDONED PERFS

10934.0 - 10976.0' ABANDONED PERFS

10: 11100¹

LOXY USA INC. CURRENT JXY TIGER FEDERAL #1 SEC 21 T20S R36E LEA NM



0.0 - 440.0' 17 1/2" OD HOLE 0.0 - 440.0' CEMENT 420sx-CIRC 0.0 - 440.0' 13 3/8" OD SURF CSG

440.0 - 5510.0' 11" OD HOLE 0.0 - 5510.0' CEMENT 2275sx 0.0 - 5510.0' 8 5/8" OD INT CSG

5510.0 - 11100.0' 7 7/8" OD HOLE 8500.0 - 11100.0' CEMENT 450sx-CBL 0.0 - 11100.0' 5 1/2" OD PROD CSG

9300.0 - 9304.0' PERFS

10934.0 - 10976.0' ABANDONED PERFS

10855.0 - 10890.0' CEMENT PLUG 5sx 10890.0 - 10890.0' CIBP

CHARLES OF THE STATE OF THE STA