

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30 025 33349
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil / Gas Lea	

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> DRY <input type="checkbox"/> OTHER <input type="checkbox"/>				7. Lease Name or Unit Agreement Name VAN ETT EN L.	
b. Type of Completion: NEW WELL <input checked="" type="checkbox"/> WORKOVER <input type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/> DIFF RES. <input type="checkbox"/> OTHER <input type="checkbox"/>					
2. Name of Operator TEXACO EXPLORATION & PRODUCTION INC.				8. Well No 18	
3. Address of Operator 205 E. Bender, HOBBS, NM 88240				9. Pool Name or Wildcat MONUMENT PADDOCK	
4. Well Location Unit Letter <u>J</u> ; <u>1650</u> Feet From The <u>SOUTH</u> Line and <u>2310</u> Feet From The <u>EAST</u> Line Section <u>9</u> Township <u>20S</u> Range <u>37E</u> NMPM <u>LEA</u> COUNTY					
10. Date Spudded 4/14/96	11. Date T.D. Reached 4/23/96	12. Date Compl. (Ready to Prod.) 5/3/96	13. Elevations (DF & RKB, RT, GR, etc.) 3540 GL	14. Elev. Csghead	
15. Total Depth 5550'	16. Plug Back T.D. 5350'	17. If Mult. Compl. How Many Zones?	18. Intervals Drilled By PRIDE	Rotary Tools	Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name 5208'-5228' MONUMENT PADDOCK				20. Was Directional Survey Made YES	
21. Type Electric and Other Logs Run PE-DLL-MSFL-LDT-, GR-CBL-CCL				22. Was Well Cored YES	

23. CASING RECORD (Report all Strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENT RECORD	AMOUNT PULLED
8-5/8"	24#	1165'	11"	500 SX, CIRC.	
5-1/2"	17#	2757'	7-7/8"	400 SX, CIRC.	
5-1/2"	15.5#	5550'	7-7/8"	1685 SX, CIRC.	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2-7/8"	5243'	

26. Perforation record (interval, size, and number)

5208'-5228' W/2JSPF 40 HOLES.

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED

5208'-5228' W/3000 GAL 15% NEFE W/60 BS

28. PRODUCTION

Date First Production 5/3/96	Production Method (Flowing, gas lift, pumping - size and type pump) PUMPING (2" X 1-1/2" X 20')				Well Status (Prod. or Shut-in) PRODUCING		
Date of Test 5-7-96	Hours tested 24	Choke Size OPEN	Prod'n For Test Period	Oil - Bbl. 200	Gas - MCF 14	Water - Bbl. 1	Gas - Oil Ratio 70
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API -(Corr.) 42.1	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

SOLD

Test Witnessed By
TOM V. SEBASTAIN

30. List Attachment
DEVIATION SURVEY

31. I hereby certify that the information on both sides of this form is true and complete to the best of my knowledge and belief.

SIGNATURE Paula S. Ives TITLE Engineering Assistant

DATE 8/8/96

TYPE OR PRINT NAME Paula S. Ives

Telephone No. 397-0432

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true verticle depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	1150'	T. Canyon
T. Salt	1300'	T. Strawn
B. Salt	2500'	T. Atoka
T. Yates		T. Miss
T. 7 Rivers		T. Devonian
T. Queen	3360'	T. Silurian
T. Grayburg	3530'	T. Montoya
T. San Andres		T. Simpson
T. Glorieta		T. McKee
T. Paddock	5272'	T. Ellenburger
T. Blinberry		T. Gr. Wash
T. Tubb		T. Delaware Sand
T. Drinkard		T. Bone Springs
T. Abo		T.
T. Wolfcamp		T.
T. Penn		T.
T. Cisco (Bough C)		T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn "B"
T. Kirtland-Fruitland	T. Penn "C"
T. Pictured Cliffs	T. Penn "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
T. Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 5208' to 5228'

No. 2, from to

No. 3, from to

No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from to feet

No. 2, from to feet

No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	1150	1150	ANHYDRITE				
1150	1300	150	SALT				
1300	2500	1200	SALT				
2500	3360	860	SAND & DOLOMITE				
3360	3530	170	DOLOMITE				
3530	5272	1742	DOLOMITE				