

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-105
Revised 1-1-89

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO. 30-025-33512
5. Indicate Type Of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG	
1a. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> DRY <input type="checkbox"/> OTHER _____	
b. Type of Completion: NEW WELL <input checked="" type="checkbox"/> WORK OVER <input type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/> DIFF RESVR <input type="checkbox"/> OTHER _____	
2. Name of Operator Amerada Hess Corporation	
3. Address of Operator P.O. Drawer D, Monument, N.M. 88265	
4. Well Location Unit Letter <u>A</u> : <u>330</u> Feet From The <u>North</u> Line and <u>660</u> Feet From The <u>East</u> Line Section <u>34</u> Township <u>19S</u> Range <u>36E</u> NMPM Lea County	
10. Date Spudded 7-26-96	11. Date T.D. Reached 8-9-96
12. Date Compl.(Ready to Prod.) 8-16-96	13. Elevations(DF & RKB, RT', GR, etc.) 3651' GR
14. Elev. Casinghead	
15. Total Depth 7493'	16. Plug Back T.D. 7397'
17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By Rotary Tools <input checked="" type="checkbox"/> Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name 7200' - 7255' & fr. 7266' - 7323'. Monument Abo	
20. Was Directional Survey Made Yes	
21. Type Electric and Other Logs Run CNL/LDT/PE/CAL/BHC/NGT, FMI/TCL, CBL	
22. Was Well Cored No	

23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	24#	1277'	11'	450 Sx. "C" Total +	Additives.
5-1/2"	15.5#	7493'	7-7/8"	200 Sx. "H" & 800 Sx.	50/50(POS:C)
				+ Additives.	
24. LINER RECORD					
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	
25. TUBING RECORD					
SIZE	DEPTH SET	PACKER SET			
2-7/8"	7150'	7150'			
26. Perforation record (interval, size, and number) Perf. w/Hyper Jet III charges w/2 SPF. total 228 shots fr. 7200' - 7255' & fr. 7266' - 7323'.					
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.					
DEPTH INTERVAL			AMOUNT AND KIND MATERIAL USED		
7200' - 7323'			Acid w/6700 gal. 15% HCl acid.		
28. PRODUCTION					
Date First Production 8-16-96		Production Method (Flowing, gas lift, pumping - Size and type pump) Flowing			Well Status (Prod. or Shut-in) Producing
Date of Test 8-28-96	Hours Tested 24	Choke Size 13/64"	Prod'n For Test Period	Oil - Bbl. 319	Gas - MCF 305
Flow Tubing Press. 490	Casing Pressure 0	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl. 0
					Gas - Oil Ratio 956
					Oil Gravity - API (Corr.)

29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold					
30. List Attachments C-102, C-103, C-104, C-105, Directional Survey, Logs					
31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief					

Signature <i>R. L. Wheeler, Jr.</i>	Printed Name <u>R. L. Wheeler, Jr.</u>	Title <u>Admin. Svc. Co.</u>	Date <u>9-5-96</u>
-------------------------------------	--	------------------------------	--------------------

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____ 1235'
 T. Salt _____ 1330'
 B. Salt _____ 2550'
 T. Yates _____
 T. 7 Rivers _____
 T. Queen _____ 3525'
 T. Grayburg _____ 3930'
 T. San Andres _____ 4370'
 T. Glorieta _____
 T. Paddock _____
 T. Blinbry _____ 5960'
 T. Tubb _____ 6790'
 T. Drinkard _____ 6870'
 T. Abo _____ 6960'
 T. Wolfcamp _____
 T. Penn _____
 T. Cisco (Bough C) _____

T. Canyon _____
 T. Strawn _____
 T. Atoka _____
 T. Miss _____
 T. Devonian _____
 T. Silurian _____
 T. Montoya _____
 T. Simpson _____
 T. McKee _____
 T. Ellenburger _____
 T. Gr. Wash _____
 T. Delaware Sand _____
 T. Bone Springs _____
 T. _____
 T. _____
 T. _____
 T. _____

Northeastern New Mexico

T. Ojo Alamo _____
 T. Kirtland-Fruitland _____
 T. Pictured Cliffs _____
 T. Cliff House _____
 T. Menefee _____
 T. Point Lookout _____
 T. Mancos _____
 T. Gallup _____
 Base Greenhorn _____
 T. Dakota _____
 T. Morrison _____
 T. Todilto _____
 T. Entrada _____
 T. Wingate _____
 T. Chinle _____
 T. Permian _____
 T. Penn "A" _____
 T. Penn. "B" _____
 T. Penn. "C" _____
 T. Penn. "D" _____
 T. Leadville _____
 T. Madison _____
 T. Elbert _____
 T. McCracken _____
 T. Ignacio Otzte _____
 T. Granite _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____
 No. 2, from _____ to _____
 No. 3, from _____ to _____
 No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet _____
 No. 2, from _____ to _____ feet _____
 No. 3, from _____ to _____ feet _____

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0'	1235'	1235'	Red Beds				
1235'	1330'	95'	Anhydrite				
1330'	2550'	1220'	Salt				
2550'	3525'	975'	Dolomite, Anhydrite, Sand				
3525'	3930'	405'	Sand, Dolomite				
3930'	7470'	3540'	Dolomite				

207 208
 19-00-000
 10-1-1966
 10-1-1966