

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I

P.O. Box 1980, Hobbs NM 88241-1980

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-33670

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

W. A. Weir

8. Well No.

12

9. Pool name or Wildcat

Monument Abo

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

Amerada Hess Corporation

3. Address of Operator

P. O. Box 840, Seminole, Texas 79360-0840

4. Well Location

Unit Letter L : 2130 Feet From The South Line and 560 Feet From The West Line

Section 35 Township 19S Range 36E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3617' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOBS ☐

OTHER: New well completion. ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11-27 thru 12-11-96

MIRU Pride Well Svc. & Star Tool. Installed BOP & TIH w/4-3/4" bit. Drld. cement fr. 6921' - 6929' & DV tool fr. 6929' - 6932'. TIH & tagged float collar at 7516'. Circ. hole clean. Tested csg. to 1000 PSI for 15 min. Held OK. Schlumberger ran USI/CCL/GR log. Schlumberger TIH w/4" csg. gun & perf. csg. at 7390' w/4 shots. TIH w/5-1/2" Halliburton EZ drill cement retainer set at 7321'. Est. rate of 2.75 BPM at 200#. Mixed & pumped 100 sks. Class "H" cement w/.5% CFR-3 followed by 300 sks. Class "H" neat cement. Displaced cement with water at 1.2 BPM. Never caught press. Est. new inj. rate at 2 BPM, 700#. Mixed & pumped 50 sks. Class "H" cement followed by 235 sks. Class "H" neat cement. WOC. TIH w/bit & tagged TOC at 7220'. Drld. cement fr. 7220', retainer at 7321' & fell through cement at 7420'. Press. tested csg. to 1000 PSI for 15 min. Held OK. Schlumberger ran GR/CCL fr. 7000' - 7509'.

CONTINUED ATTACHED

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

R. L. Wheeler, Jr.

TITLE Admin. Svc. Coord.

DATE 1-3-97

TYPE OR PRINT NAME R. L. Wheeler, Jr.

TELEPHONE NO. 915 758-6778

(This space for State ORIGINAL SIGNED BY USER OR NOTARIAL)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JAN 07 1997

