Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103

Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240	OIL CONSERVATION DIVISION 310 Old Santa Fe Trail, Room 206 Santa Fe, New Mexico 87503		WELL API NO. 30-025-33697
DISTRICT II P.O. Drawer DD, Artesia, NM 88210			5. Indicate Type of Lease
DISTRICT III 1000 Rio Brazos Rd., Azzec, NM 87410			STATE X FEE 6. State Oil & Gas Lease No. V-2021
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name
1. Type of Well: OIL OAS WELL X WELL	OTHER		Conoco State
2. Name of Operator	Onex		8. Well No.
Stevens & Tull, 3. Address of Operator	Inc.		2 9. Pool name or Wildcat
P.O. Box 11005,	Midland, TX 79702		West Teas Y-SR
Unit Letter D : C90 Feet From The North Line and 990 Feet From The Line			
Section 16	10. Elevation (Show whether		NMPM Lea County
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO: Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT		
		CASING TEST AND CE	است
OTHER:			nt Surface Casing x
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed			
work) SEE RULE 1103. 12/30/96 - Spuć 12 1/4" hole at 5:00 p.m. MST			
1/1/97 - TD 12 1/4" hole at 1325'. Run 30 joints - 8 5/8" - 24# - J55 casing to 1312'. Cement with 650 sx "c" plus 4% gel plus 2% CaCl plus 1/4# celloflake tail with 150 sx "c" plus 2% CaCl. Circulated 257 sx cement to surface.			
1/2/97 - WOC for 12 hours with 500 psi on casing. WOC additional 12 hours before drill out - total 24 hours - test BOP's to 2,000 psi.			
1/3/97 - Begin drilling 7 7/8" hole.			
			er .
I hereby certify that the information above is true a	d accordate to the heat of our broadedes and hal		
SIGNATURE 17 Holes 19		LE Consulting H	Engineer DATE 1/9/97
			TELEPHONE NO. 915/699-1410
(This space for State Use)			
ADDROUTED BY		ı .	JAN 22 1397

