

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all specific tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in triplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____
 T. Salt _____
 B. Salt _____
 T. Yates _____ 3704.0
 T. 7 Rivers _____ 3908.0
 T. Queen _____
 T. Grayburg _____
 T. San Andres _____ 4946.0
 T. Glorieta _____
 T. Paddock _____
 T. Blinebry _____
 T. Tubb _____
 T. Drinkard _____
 T. Abo _____
 T. Wolfcamp _____ 10320.0
 T. Penn _____
 T. Cisco (Bough C) _____

T. Canyon _____
 T. Strawn _____ 10576.0
 T. Atoka _____ 10794.0
 T. Miss _____
 T. Devonian _____
 T. Silurian _____
 T. Montoya _____
 T. Simpson _____
 T. McKee _____
 T. Ellenburger _____
 T. Gr. Wash _____
 T. Delaware Sand _____
 T. Bone Springs _____ 7667.0
 T. Rustler _____ 1898.0
 T. Delaware _____ 5496.0
 T. 1st Bone Spring SS _____ 8720.0
 T. 2nd Bone Spring SS _____ 9356.0

Northwestern New Mexico

T. Ojo Alamo _____
 T. Kirtland-Fruitland _____
 T. Pictured Cliffs _____
 T. Cliff House _____
 T. Menefee _____
 T. Point Lookout _____
 T. Mancos _____
 T. Gallup _____
 Base Greenhorn _____
 T. Dakota _____
 T. Morrison _____
 T. Todilto _____
 T. Entrada _____
 T. Wingate _____
 T. Chinle _____
 T. Permian _____
 T. Penn. "A" _____

T. Penn. "B" _____
 T. Penn. "C" _____
 T. Penn. "D" _____
 T. Leadville _____
 T. Madison _____
 T. Elbert _____
 T. McCracken _____
 T. Ignacio Otzte _____
 T. Granite _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____
 No. 2, from _____ to _____
 No. 3, from _____ to _____
 No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet _____
 No. 2, from _____ to _____ feet _____
 No. 3, from _____ to _____ feet _____

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
1898.0	3704.0	1806.0	Anhydrite, Dolomite				
3704.0	3908.0	204.0	Anhydrite, Sand, Dolomite				
3908.0	4946.0	1038.0	Dolomite, Sand			10196.0	S.E. New Mexico (Cont)
4946.0	5496.0	550.0	Sand, Dolomite			10934.0	3rd Bone Spring SS
5496.0	7667.0	2171.0	Dolomite, Sand, Limestone, Shale			11258.0	Morrow
7667.0	8720.0	1053.0	Limestone, Shale, Chert				Morrow Sand
8720.0	9356.0	636.0	Limestone, Sand, Shale, Chert				
9356.0	10196.0	840.0	Limestone, Sand, Shale, Dolomite				
10196.0	10320.0	124.0	Limestone, Sand, Dolomite				
10320.0	10576.0	256.0	Limestone, Sand, Shale				
10576.0	10794.0	218.0	Limestone, Chert, Shale				
10794.0	10934.0	140.0	Sand, Limestone				
10934.0	11258.0	324.0	Limestone, Dolomite, Shale, Chert				

