

UNITED  
DEPARTMENT OF  
BUREAU OF LAND

## APPLICATION FOR PERMIT

OPER. CONNO. 1071 L  
PROPERTY NO. 1699  
POOL CODE 37584  
EXP. DATE 3/19/97  
APPRO. 30-225-33885ATE\*  
onFORM APPROVED  
OMB NO. 1004-0136  
Expires: February 28, 1995

## 1a. TYPE OF WORK

DRILL ☒DEEPEN ☐

## b. TYPE OF WELL

OIL  
WELL ☒GAS  
WELL ☐

OTHER

SINGLE  
ZONE ☐MULTIPLE  
ZONE ☐

## 2. NAME OF OPERATOR

Read &amp; Stevens, Inc.

505/622-3770

## 3. ADDRESS AND TELEPHONE NO.

P. O. Box 1518

Roswell, NM 88202

## 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)\*

At surface

990' FNL &amp; 990' FWL

At proposed prod. zone

Same

Unit D

## 14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE\*

30 miles SW of Hobbs, NM

16. DISTANCE FROM PROPOSED\*  
LOCATION TO NEAREST  
PROPERTY OR LEASE LINE, FT.  
(Also to nearest drig. unit line, if any)

990'

18. DISTANCE FROM PROPOSED LOCATION\*  
TO NEAREST WELL, DRILLING, COMPLETED,  
OR APPLIED FOR, ON THIS LEASE, FT.

1320'

## 16. NO. OF ACRES IN LEASE

320

## 19. PROPOSED DEPTH

8,400'

17. NO. OF ACRES ASSIGNED  
TO THIS WELL

40

## 20. ROTARY OR CABLE TOOLS

Rotary

## 21. ELEVATIONS (Show whether DF, RT, GR, etc.)

3656' GL

## 22. APPROX. DATE WORK WILL START\*

April 15, 1997

## 23.

SECRETARY'S POTASH

PROPOSED CASING AND CEMENTING

CAPTAIN COUNTRY TO WATER BASIN

SIZE OF HOLE	GRADE SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
17 1/2"	13 3/8" J-55	54.5#	1600'	Circ 1000 <del>WITNESS</del> + 200 "C"
11"	8 5/8" S-80	32.0#	5000'	Circ 1100 sx ** See Note
7 7/8"	5 1/2" N-80	17.0#	8400'	Tieback w/500 or 975 sx*

## Mud Program:

0' - 1600': Fresh water native mud:  
1600' - 5000': Brine mud:  
5000' - 8400': Fresh water mud w/starch:

## Mud Wt.

8.4 ppg  
10.0 ppg  
8.8 ppg

## Vis.

32  
28-32  
32-40

## W/L Control

No W/L control  
No W/L control  
W/L control 15 cc

## BOP Program:

A 11" 5000 psi wp Shaffer Type LWS BOP, with a 5000 psi wp 11" GK Hydril, will be installed on the 13 3/8" casing. Casing and BOP will be tested before drilling out with 11". BOP will be tested daily as 3000 psi wp system.

\* NOTE: If severe lost circulation is not encountered, hole will be reduced at 5000' to 7 7/8" and drill ahead WITHOUT setting the 8 5/8" casing.

\*\* 8 5/8": Cement with DV tool in two stages starting at 3800':

1st stage: Lead 200 sx lite, tail in w/200 sx "C".

2nd stage: Lead 500 sx lite cement, tail w/200 sx "C". Cement to surface

APPROVAL SUBJECT TO:  
GENERAL REQUIREMENTS AND  
SPECIAL STIPULATIONS  
ATTACHED

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

## 24.

Agent for:

Read &amp; Stevens, Inc.

Jan. 31, 1997

SIGNED

*George Smith*

TITLE

(This space for Federal or State office use)

PERMIT NO.

APPROVAL DATE

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  
CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY

*John F. Smith*

TITLE

*Asst. State Director*

DATE

*3-2-97*

\*See Instructions On Reverse Side

4457

RECEIVED  
JAN 10 1964  
U.S. AIR FORCE  
HONOLULU, HAWAII

