

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs NM 88241-1980

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-33982

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

Amerada Hess Corporation

3. Address of Operator

P. O. Box 840, Seminole, Texas 79360-0840

7. Lease Name or Unit Agreement Name

North Monument G/SA Unit #1524

8. Well No.

NMOCD No. 291

9. Pool name or Wildcat

Eunice Monument Grayburg San Andres

4. Well Location

Unit Letter H : 1330 Feet From The North Line and 1220 Feet From The East Line

Section

31

Township

19S

Range

37E

NMPM

Lea

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3581' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: New Well Completion. ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-2 thru 7-11-97

MIRU Tyler Well Svc. & Star Tool. Installed BOP & TIH w/6-1/8" bit tagged at 3820'. Drld. wiper plug, float collar & cement to 3897'. Circ. clean & press. tested 7" csg. to 1850# for 30 min. Held Ok. Drld. cement fr. 3897' - 3902' & shoe to 3904'. Drld. new Open Hole fr. 3904' - 4025'. Schlumberger ran GR/CNL/CCL & USIT. Halliburton spotted total of 140 sks. Class "H" cement w/2#/sk. Calseal, 1#/sk. KCL, & 0.5% Halad-344 plug fr. 4025' - 3860' in 5 trips. WOC. TIH w/6-1/8" bit & tagged cement at 3860'. Drld. cement fr. 3860' - 3930'. Circ. hole clean. Schlumberger perf. 7" csg. in Eunice Monument Grayburg San Andres Zone using 4" Hogs gun w/2 SPF, total 191 holes at following intervals: 3773' - 3812', 3824' - 3835', & fr. 3846' - 3890'. Tagged PBTD at 3930'. Halliburton Svc. acidized Grayburg San Andres Zone 7" csg. perfs. fr. 3773' - 3890' & Open Hole fr. 3904' - 3930' w/5900 gal. 15% HCL w/0.6% Fercheck SC acid w/5 gal./1000 SCA. Swabbed well.

CONTINUED ATTACHED

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

R. L. Wheeler, Jr.

TITLE Admin. Svc. Coord.

DATE 7-22-97

TYPE OR PRINT NAME R. L. Wheeler, Jr.

TELEPHONE NO. 915 758-6778

(This space for State Use)

ORIGINAL SIGNED BY CHRIS WILLIAMS
DISTRICT I SUPERVISOR

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

AUG 08 1997