

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-34042
5. Indicate Type of Lease	STATE ☒ FEE ☐
6. State Oil / Gas Lease No.	
7. Lease Name or Unit Agreement Name	NEW MEXICO 'E' STATE NCT-2
8. Well No.	3
9. Pool Name or Wildcat	MONUMENT ABO

SUNDY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.	
1. Type of Well:	OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. Name of Operator	TEXACO EXPLORATION & PRODUCTION INC.
3. Address of Operator	205 E. Bender, HOBBS, NM 88240
4. Well Location	Unit Letter <u>C</u> : <u>800</u> Feet From The <u>NORTH</u> Line and <u>1650</u> Feet From The <u>WEST</u> Line Section <u>23</u> Township <u>19-S</u> Range <u>36-E</u> NMPM <u>LEA</u> COUNTY
10. Elevation (Show whether DF, RKB, RT,GR, etc.)	3733

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
 PULL OR ALTER CASING ☐
 OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
 COMMENCE DRILLING OPERATION ☐ PLUG AND ABANDONMENT ☐
 CASING TEST AND CEMENT JOB ☐
 OTHER: ☒ SPUD & SURFACE CSG

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-04-99: SPUD WELL @ 9:15 PM 12/03/99 DRILL TO 285, 583', 613, 673, 1162, 1330. RU CSG CREW & RUN 30 JTS 8 5/8" 28# NS-55 LTC CSG SET @ 1330'. INSERT FLOAT @ 1285'. CENTRALIZED BTM 3 JTS & EVERY 4TH JT TO SURF. CMT W/780 SX CL C & 2% D20 @ 2% S1 MIXED AT 14.2 PPG, YIELD 1.5 FOLLOWED BY 150 SX CL C @ 2% S1 MIXED @ 14.8 PPG, YIELD 1.34. DISPL W/81 BFW. NUBOP.PU BHA #2 & TIH. TAG CMT @ 1224'. DRILL CMT @ 1280', 1300, 1330, 1390, 1825, 2322, 2740, 2820, 2974, 3128, 3502, 3627, 3782, 3876, 3963, 4002, 4159, 4284, 4328, 4441, 4566, 4692, 4743, 4838, 4887, 5016, 5034, 5146, 5152, 5193, 5204, 5365. RUN GYRO. HORIZ DISP @ 5333 IS 133.16' IN DIRECTION OF 80.61 DEG. GYRO SURVEY @ 5333. DRILL FR 5365-5598, 5650, 5726, 6036, 6047, 6159, 6169, 6236, 6295. TIH & TEST MWD TO 5505. SURV W/MWD. TIH TO 5691. SLIDE DRILL 6295-6307, 6340, 6372, 6419, 6437, 6481, 6492, 6579, 6589, 6627, 6638, 6650, 6698, 6760, 6837. ROTATE DRILL FR 6837-6854, 6860, 6865, 6916, 7009, 7060, 7096, 7103, 7195, 7290, 7302, 7353, 7365, 7383, 7445, 7506. CIRC @ TD.SDI RELEASED @ 1:30 AM 12/24/99. RUN PLEXP LOG.INSTL FLOWLINE.TIH W/DC'S.TAG STUCK PIPE @ 7238'. TIH TO 7506.CIRC & POT 28 BBLs 2 PPG 16/30 OTTAWA SD. TAD 1ST SAND STAGE @ 7469'. SPOT TBG @ 7199'. PUMP 2ND SAND STAGE 3420 LBS SD IN 1000 GEL BRINE. TAG 2ND SD STG @ 7381'. SPOT TBG @ 7106'. PMP 3 RD SAND STAGE 3200 LBS SD IN 1000 GEL BRINE. TAG 3RD SD STG @ 7292'. SPOT TBG @ 7013'. PMP 4TH SD STG 3500 LBS SD IN 1000 GEL BRINE. WSH SD TO 7190. LDDP & 3 1/2" TBG.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE J. Denise Leake TITLE Engineering Assistant

DATE 12/26/99

TYPE OR PRINT NAME J. Denise Leake

Telephone No. 397-0405

(This space for State Use)


APPROVED

BY CHRIS WILLIAMS

TITLE

DISTRICT I SUPERVISOR

DATE



NEW MEXICO 'E' STATE PT-2 #3
Report: 2 12/5/99

99 Texaco Inc. - All Rights Reserved
ILLING REPORT
Proprietary Information of Texaco Inc.

CASING REPORT

Casing String: SURFACE		Run Date: 12/5/99		Shoe Depth: 1330		Float Collar Depth: 0		DV Tool Depths: 0		0
Section	Prop. Size	Actual Size	Grade	Weight	Connection	Joints	Length	Prop. Depth	Actual Depth	
1	8.625	8.625	NS-55	28	LTC	30	1316	1330	1330	



CEMENT REPORT

String:	SURFACE		Start Date:	12/6/99	
Stage:	1		Start Time:	12/30/99	
	"Lead"	"Tail"		"Lead"	"Tail"
Cement Type:	C	C	Slurry Volume (ft³):	1170	201
Cement Top (ft):	0	0	Thickening Time (h.min)	0	0
Slurry Weight (ppg):	14.2	14.8	Free Water (cc/30m):	0	0
Mix Water (gal/sx):	7.45	6.31	Fluid Loss (cc/30m):	0	0
Water Type:	FRESH	FRESH	Comp Str (psi):	0	0
Yield (ft³/sx):	1.5	1.34	Comp Str (h.min):	0	0
Sacks:	780	150			
Lead Additives:	CLASS C + 2% D20 + 2% S1		Tail Additives:	CLASS C + 2% S1	
Comment:	CIRC 81 BBLS OR 303 SX CMT TO SURFACE.				