State of New Mexico

Form C-103 Submit 3 Copies Energy, Minerals and Natural Resources Department to Appropriate Revised 1-1-89 District Office DISTRICT I OIL CONSERVATION DIVISION WELL API NO. P.O. Box 1980, Hobbs, NM 88240 310 Old Santa Fe Trail, Room 206 30-025-34364 DISTRICT II Santa Fe, New Mexico 87503 P.O. Drawer DD, Artesia, NM 88210 5. Indicate Type of Lease STATE FEE __ DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. 23178 **SUNDRY NOTICES AND REPORTS ON WELLS** (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) Type of Well: Indiana "1" OIL. X WELL. 2. Name of Operator 8. Well No. Sahara Operating Company 3. Address of Operator 9. Pool name or Wildcat P.O. Box 4130, Midland, TX Goodwin (Abo) Well Location 1682 North 1975 East Unit Letter _ Feet From The Line and Feet From The Line 19 South 36 East Lea Section Township Range **NMPM** 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3751 KB Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK **ALTERING CASING** TEMPORARILY ABANDON **CHANGE PLANS** COMMENCE DRILLING OPNS. **PLUG AND ABANDONMENT PULL OR ALTER CASING** CASING TEST AND CEMENT JOB X OTHER: OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 6/5/98 Drilled to 1550'. Circ hole, TOH. RU Csg Crew & ran 35 its new 8-5/8". 24 lb/ft, K-55, ST&C casing w/notched guide shoe on bottom, float collar 1 jt up. Dressed casing w/10 centralizers. RU BJ Services & cemented with $600~\rm sx~Class"C"~w/4\%~gel,~2\%~CaCl2~\&~1/4~lb/sk~celloflake,$ tailed in with 200 sx Class "C" w/2% CaCL2. Plug down @9:30 AM, 6-4-98. Circulated 218 sx to pit. WOC. Cut off casing, NU BOP. Tested Blind rams & casing to 1500# for 30 min OK. TIH w/BHA. Tested Pipe rams to 1500# OK. Cement set 12 hrs before casing test, 18 hrs before drill out.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE THUE President	DA	ATE 5:45. 98
TYPEOR PRINT NAME Robert McAlpine	тегенкоме NO. 915/69	97-0967

(This space for State Use)

ORIGINAL SIGNED BY CHRIS WILLIAMS DISTRICT I SUPERVISOR

JUN 10 1998

APPROVED BY ---

CONDITIONS OF APPROVAL, IP ANY: