

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly drilled or deepened well. It shall be accomplished by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	1832	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	1952	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	3308	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	3588	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	3808	T. Devonian	T. Menefee	T. Madison
T. Queen		T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg		T. Montoya	T. Mancos	T. McCracken
T. San Andres		T. Sipson	T. Gallup	T. Ignacio Otzte
T. Glorieta		T. McKee	Base Greenhorn	T. Granite
T. Paddock		T. Ellenburger	T. Dakota	T.
T. Blinbry		T. Gr. Wash	T. Morrison	T.
T. Tubb		T. Delaware Sand	T. Todilto	T.
T. Drinkard		T. Bone Springs	T. Entrada	T.
T. Abo		T.	T. Wingate	T.
T. Wolfcamp		T.	T. Chinle	T.
T. Penn		T.	T. Permian	T.
T. Cisco (Bough C)		T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from to.....

No. 2, from to.....

No. 3, from to.....

No. 4, from to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet

No. 2, from to feet

No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology
0	1600	1600	Redbeds
1600	1952	352	Shale & Anhydrite
1952	3308	1456	Salt & Anhydrite
3308	4900	3259	Anhydrite, Sand, Dolomite