NMOCD Holds

UNITED STATES Form 3160-5 FORM APPROVED (June 1990) Budget Bureat No. 1004-0135 DEPARTMENT OF THE INTERIOR Expires: March 31, 1993 BUREAU OF LAND MANAGEMENT 5. Lease Designation and Serial No. NM-100565 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well Oil Well Other 8. Well Name and No. 2. Name of Operator GOB "33" Fed #1 9. API Well No. OGS Operating Co., Inc. 3. Address and Telephone No. 30-025-34627 10. Field and Pool, or Exploratory Area 550 W. Texas, Suite 1140 Midland, Texas 79701 915-682-6373 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Lynch Yates- 7 Rivers 1650' FNL & 2080' FEL, Sec 33, T-20-S, R-34-E 11. County or Parish, State Lea, New Mexico 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION → Notice of Intent Abandonment Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other Progress Report Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 7-20-99 Drilling @ 690' Spud @ 7:00 PM 7-19-99 3/4°@ 500' Drilling @ 1630' 1/4°@942' 7-21-99 7-22-99 Set 8.5/8" casing @ 1627' cemented with 780sx. Circ. 159sx cmt. 7-23-99 Drilling @ 1960' Tested BOP's & Choke manifold to 1500 psi 7-24-99 Drilling @ 3115' MW 10.0 PPG 1° @ 3039' 7-25-99 POH to log @ 3800' MW 10.0 PPG 1 3/4° @ 3800' 7-26-99 Logged @ 3800' Ran PEX & NGR-S Drilled to 3874, Circ. 7-27-99 Spot Plug #1 130 sx, 3874-3300, Plug #2 40sx 1675-1575' Tag @ 1512', Spot Plug #3 120 sx 350'-0. Cut off well head & install dry hole marker. Well plugged and abandoned. Approved as to plugging of the well bore Liability under bond is retained until surface restoration s completed.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Tide Drilling Superintendent

PETROLEUM ENGINEER

men

(ORIG. SGD.) LES BABYAK

(,

de

Date _7-30-99

AUG 0 4 1999