DISTRICT II

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

P.O. Drawer DD, Artesia, NM 88210

OIL CONSERVATION DIVISION

2040 Pacheco St. Santa Fe, NM 87505

WELL API NO.	
30-025-34726	
Indicate Type of Lease	

<u>DISTRICT III</u> 1000 Rio Brazos Rd., Aztec, NM 87410						STATE	FEE	
					«State Oil & Gas Lease No. V-2199			
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)				7Lease Name or Unit Agreement Name 002314				
Type of Well: OIL WELL	GAS WELL		OTHER			Gem, 8705 JV-P		
aName of Operator BTA OIL PRODUCE	RS	OGRID #003	002			•Well No.		
Address of Operator 104 SOUTH PECOS,	MIDLAND, T	X 79701				∘Pool name or Wildcat Teas, Delaware		
-Well Location Unit Letter	1650	Feet From The	South	Line and	330	Feet From The	West	Line
Section	2	Township	20 S	Range	33 E	NMPM	Lea	County
ه التيميل الدوليون الدواع موليد في دا التفاعل في الدوليون والدوليون. والموافق إلى الدوليون الدوليون الموافق الموافق الموافق الموافق الموافق المواديد. المنطق القداء الراس والدا الموافق الموافق الموافق الموافق الموافق الدواع المواديد.		10Elevation	n (Show whether R 3598' RKE	DF, RKB, RT, GR, e	etc.)			
44	OI I - A -							

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PLUG AND ABANDON PERFORM REMEDIAL WORK REMEDIAL WORK ALTERING CASING **TEMPORARILY ABANDON CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ANBANDONMENT **PULL OR ALTER CASING CASING TEST AND CEMENT JOB** OTHER: OTHER:

12Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

PATTERSON DRILLING COMPANY- Rig #49, P. O. Drawer 1416, Snyder, TX 79550

11/22/99 Spudded @ 1:00 AM - Drlg 17-1/2" hole in suface rock w/ spud mud

11/25/99 Depth 1,362' Circ & POH. Cmt'd 13-3/8" (30 jts 54.5# J55 STC) csg @ 1,362 w/ 1300 sx. Cmt circ. WOC.

11/26/99 WOC 12 hrs, installed csg head & BOP's. Cleaned out to shoe. Tested BOP's & csg to 1000 psi for 30 minutes on fresh water - OK. WOC 24 hrs total, then drld shoe. Drlg 12-1/4" hole in anhydrite & salt w/ brine.

11/29/99 Depth 2,393' Drig 12-1/4" hole in anhydrite & salt w/ brine.

I hereby certify that the in	formation above is true and complete to the best of the know	Medge and belief.				
SIGNATURE	rolly stolleller	TITLE Regulatory Administrator	DATE 11-29-99			
TYPE OR PRINT NAME D	OROTHY HOUGHTON		TELEPHONE NO. 915/682-3753			
(This space for State Use)	ORIGINAL SIGNED BY CHRIS WILLIAMS DISTRICT I SUPERVISOR		7 - 8 188			
APPROVED BY-		TITLE	DATE			
CONDITIONS OF APPROVAL, IF ANY:						

