State of New Mexico /, Minerals and Natural Resources Departm En.

Form C-103 Revised 1-1-89

DICTRICT

11.

12.

P.O. Box 1980, Hobbs, NM 88241	OIL CONSERVATION DIVISION	WELL API NO.
DISTRICT II	2040 Pacheco St.	30-025-35128
P.O. Box Drawer DD, Artesia, NM 88210	Santa Fe, NM 87505	5. Indicate Type of Lease STATE FEE
DISTRICT III		
1000 Rio Brazos Rd., Aztec, NM 87410		6. State Oil / Gas Lease No.
SUNDRY NOTICE		
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		7. Lease Name or Unit Agreement Name North Monument G/SA Unit Blk. 16, No.
1. Type of Well OIL GAS WELL WELL	OTHER	18
2. Name of Operator Amerada I	less Corporation	8. Well No. 294
3. Address of Operator P.O. Box 8	9. Pool Name or Wildcat Eunice Monument G/SA	
4. Well Location		
Unit LetterC	112 Feet From The North Line and 2622	Feet From The <u>West</u> Line
Section 32	Township 19S Range 37E N	MPM Lea COUNTY
	10. Elevation (Show whether DF, RKB, RT,GR, etc.) 3594' GL	, 3607' KB

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK		PLUG AND ABANDON		REMEDIAL WORK ALTERING CASING	
TEMPORARILY ABANDON		CHANGE PLANS		COMMENCE DRILLING OPERATIONS PLUG AND ABANDONMENT	П
PULL OR ALTER CASING				CASING TEST AND CEMENT JOB	_
OTHER:		<u>-</u>	🗆	OTHER: New Well Completion.	~
					

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-6 thru 10-20-2000

MIRU Key Well Svc. pulling unit & installed BOP. TIH w/4-3/4" bit & tagged wiper plug at 3840'. Drld. wiper plug, float collar & cement to 3925' & circ. clean. Schlumberger ran USIT Log. Schlumberger TIH w/4" csg. gun & perf. 5-1/2" csg. in Grayburg San Andres Zone w/2 SPF, total 244 holes, at following intervals: 3683'-3687', 3742'-3758', 3770'-3782', 3796'-3803', 3807'-3835', 3843'-3862', 3872'-3887', & fr. 3897'-3914'. B.J. Svc. acidized Grayburg San Andres Zone csg. perfs. fr. 3683'-3914' w/6100 gal. 15% HCL acid. Swabbed well. TIH w/2-7/8" tbg. Set OE at 3908'. Removed BOP & installed wellhead. TIH w/2-1/2" x 2" RHBC 20' x 3' x SO' pump on rods. RDPU & cleaned location. Set pumping unit & motor. Connected electrical service & began pumping well 10-20-2000

Test of 11-1-2000: Prod. 136 B.O./D., 33 B.W/D., & 12 MCFGPD in 24 hours.

I hereby certify that the information above is true one complete to the dest of my knowledge and belief. SIGNATURE TITLE Bus. Svc. Spec. II	DATE11/15/2000
TYPE OR PRINT NAME Roy L. Wheeler, Jr.	TELEPHONE NO. 915-758-6778
(This space for State Use) ORIGINAL SIGNED BY CHRIS WILLIAM* APPROVED BY USTRICT SUPPRINTSOF TITLE	DATE