

**DISTRICT I**

P.O. Box 1980, Hobbs, NM 88241

**DISTRICT II**

P.O. Box Drawer DD, Artesia, NM 88210

**DISTRICT III**

1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**

2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO.	30-025-35181
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil / Gas Lease No.	B-1431-3
7. Lease Name or Unit Agreement Name	North Monument G/SA Unit
8. Well No.	930
9. Pool Name or Wildcat	Eunice Monument G/SA
10. Elevation (Show whether DF, RKB, RT,GR, etc.)	3616' GL, 3629' KB

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well	OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator	Amerada Hess Corporation
3. Address of Operator	P.O. Box 840, Seminole, TX 79360
4. Well Location	Unit Letter <u>N</u> : <u>224</u> Feet From The <u>South</u> Line and <u>2443</u> Feet From The <u>West</u> Line Section <u>25</u> Township <u>19S</u> Range <u>36E</u> NMPM <u>Lea</u> COUNTY
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPERATIONS ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☒ New well completion.

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-4 thru 12-15-2000

MIRU Key Well Svc. pulling unit & installed BOP. TIH w/6-1/4" bit, tagged float collar at 3976' & drld. out float collar & cement to 4040' & circ. clean. Schlumberger ran USIT Log. Schlumberger TIH w/4" csg. gun & perf. 7" csg. in Grayburg San Andres Zone w/2 SPF, total 193 holes, at following intervals: 3772' - 3781', 3806' - 3815', 3825' - 3834', 3858' - 3873', 3886' - 3890', 3894' - 3898', 3904' - 3906', 3929' - 3933', 3940' - 3950', 3960' - 3968', 3981' - 3993', & fr. 4004' - 4010". B.J. Svc. acidized csg. perfs. fr. 3772'-4010' w/4200 gal. 15% HCL acid. Swabbed well. TIH w/2-7/8" tbg. set OE at 4012' w/TAC at 3725'. Removed BOP & installed wellhead. TIH w/2-1/2" x 2" RHBC 20' x 3' x SO' pump on rods. RDPU & cleaned location. Set pumping unit & motor. Connected electrical service & began pumping well 12-15-2000.

Test of 1-2-2001: Produced 0 B.O./D., 444 B.W./D., & 5 MCFGPD in 24 hours.

\*Note: Bottomhole location is 6' FSL & 2634' FEL, Unit O, Sec. 25, T19S, R36E.  
Bottom of completion is located 15' FSL & 2640' FEL, Unit N, Sec. 25, T19S, R36E.  
This well is located in interior of North Monument Grayburg San Andres Unit Boundary.

2652'w

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Roy L. Wheeler, Jr. TITLE Bus. Svc. Spec. II DATE 01/04/2001  
TYPE OR PRINT NAME Roy L. Wheeler, Jr. TELEPHONE NO. 915-758-6778

(This space for State Use)

APPROVED BY ORIGINAL OF STATE OF NEW MEXICO WILLIAMS TITLE DISTRICT I SUPERVISOR DATE JAN 16 2001  
CONDITIONS OF APPROVAL, IF ANY: