## State of New Mexico Er , Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

FEE

<u>DISTRICT |</u> P.O. Box 1980, Hobbs, **NM** 88240 OIL CONSERVATION DIVISION

	204
DISTRICT II	San
P.O. Drawer DD, Artesia, NM 88210	

2040 Pacheco St. Santa Fe, NM 87505 WELL API NO.
30-025-35510
sIndicate Type of Lease

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 STATE X

						Soldie On & Gas Leas	e No.	
DIFFEREN	Y NOTICES A FOR PROPOSAL T RESERVOIR. ( FORM C-101) FO	S TO DRILL OI JSE "APPLICA	R TO DEEP	EN OR BLUG DAG	CK TO A	7Lease Name or Unit	Agreement Name	
Type of Well: OIL GAS WELL WEI	Σ	ОТН	ER			Simms 35 State		
<sup>2</sup> Name of Operator Nearburg Producing Comp	pany					«Well No.		
3Address of Operator 3300 N A St., Bldg 2, Suite	120, Midland, 1	X 79705				Pool name or Wildcat		
4Well Location						Osudo Morrow, V	vest	
Unit Letter N :	660 Feet From	m The	South	Line and	1980	Feet From The	West	Line
Section	35 Tow	nship	208	Range	35E	NMPM	Lea	County
		3688' GR		DF, RKB, RT, GR, etc	2.)			
11 Ch	ook Anneand	-4- D					- Control of the Cont	A CONTRACTOR OF THE CONTRACTOR

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE	OF IN I	ENTION TO:	SUBSEQUENT	REPORT OF	
PERFORM REMEDIAL WORK		PLUG AND ABANDON	 REMEDIAL WORK	ALTERING CASING	
TEMPORARILY ABANDON		CHANGE PLANS	 COMMENCE DRILLING OPNS.	PLUG AND ANBANDONMENT	
PULL OR ALTER CASING			CASING TEST AND CEMENT JOB	-	
OTHER:			OTHER: Surface casing and cemen	_	•
12Describe Proposed or Completed	Operations (	learly state all portinget details			١

12Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

08/22/01: TD 8-3/4" hole to 13,500'.

08/26/01: C&C hole. RU and ran 325 jts 5-1/2", 20#, 17#, S95, N80, LT&C & BT&C casing to 13,513'. Cement 1st stage casing using 420 sx 35/65 poz "H" + 370 sx Class "H". Circ 100 sx to surface. Cement 2nd stage using 1250 35/65 poz "H"+ additives and 100 Class "H" + additives. Circ 354 sx to surface. Cement 3rd stage using 664 35/65 poz "H" + additives and 100 sx Class "H" neat. Circ 25 sx to surface. NDBOPE, set slips, cut off casing and jet pits. Release rig on 08/27/01.

I hereby certify that the information above is true and complete to the best	or my knowledge and belief.	
SIGNATURE Kin Stewart	TITLE Regulatory Analyst	DATE 08-28-01
TYPE OR PRINT NAME Kim Stewart  (This space for State Use)		TELEPHONE NO. 915/686-8235
APPROVED BY	1 (31)	db. Alia 1.2.20