

DISTRICT I

P.O. Box 1980, Hobbs, NM 88241

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO. 30-025-35617	
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>	
6. State Oil / Gas Lease No. B1962-1	
7. Lease Name or Unit Agreement Name North Monument G/SA Unit Blk. 11, No. 22	
8. Well No. 317	
9. Pool Name or Wildcat Eunice Monument G/SA	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3598' GR	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Amerada Hess Corporation
3. Address of Operator P.O. Box 840, Seminole, TX 79360
4. Well Location Unit Letter <u>K</u> : <u>2490</u> Feet From The <u>South</u> Line and <u>2600</u> Feet From The <u>West</u> Line Section <u>29</u> Township <u>19S</u> Range <u>37E</u> NMPM <u>Lea</u> COUNTY
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3598' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPERATIONS ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☒ New Well Completion.

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8-27 thru 9-6-2001

MIRU Aries Well Svc. & installed BOP. TIH w/4-3/4" bit, tagged top of float collar at 3910' & drld. out float collar & cement to 3950', (DOD), circ. clean. Schlumberger ran USIT log. Schlumberger TIH w/4" csg. guns & perf. 5-1/2" csg. in Eunice Monument G/SA Zone w/2 SPF, total 198 holes, at following intervals: 3751'-3760', 3782'-3790', 3802'-3804', 3820'-3836', 3841'-3851', 3858'-3864', 3872'-3891', 3898'-3914', 3921'-3927', & fr. 3929'-3931'. Acidized perfs. fr. 3751' - 3931' w/4700 gal. 15% HCL acid. Swabbed well. TIH w/TAC on 2-7/8" tbg. & set tbg. OE at 3934'. Removed BOP & installed wellhead. TIH w/2-1/2" x 2" RHBC 20' x 3' x HO' pump on rods. RDPU & cleaned location. Set pumping unit & motor. Connected electrical svc., ran flowline, & began pumping well 9-6-2001.

Test of 9-8-2001: Prod. 10 B.O/D., 188 B.W/D., & 12 MCFGPD in 24 Hours. Csg. & tbg. press. 35 PSI.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Roy L. Wheeler, Jr. TITLE Bus. Svc. Spec. II DATE 09/26/2001
TYPE OR PRINT NAME Roy L. Wheeler, Jr. TELEPHONE NO. 915-758-6778

(This space for State Use)

APPROVED BY _____ TITLE _____ ORIGINAL SIGNED BY _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

PAUL E. KAUTZ
PETROLEUM ENGINEER