

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator W. K. Byrom		8. Farm or Lease Name Humble- Laughlin Battery 2
3. Address of Operator P. O. Box 147 - Hobbs, New Mexico 88240		9. Well No. 2
4. Location of Well UNIT LETTER <u>I</u> , 1980 FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>4</u> TOWNSHIP <u>20S</u> RANGE <u>37E</u> NMPM.		10. Field and Pool, or Wildcat Middle-San Andres
15. Elevation (Show whether DF, RT, GR, etc.) 3553 GL		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1-5-70:
Rigged up and prepared to deepen well but had a hole in the casing. Found holes and fixed them, tested casing to 700#. Casing held. Went back in well with drill pipe and 6-1/8" bit, drilled out to 4328.

Ran 800' of 4 1/2" 9.5# liner, cemented with 80 sacks. Perforated (4138,4144,4154) (4170,4180-82; 4190-92) (4226-28 and 4235). Swabbed each zone natural between packer an retrievable plug, the zone at 4226 to 4235 swabbed all water and from 4170 to 4192, also swabbed water. Moved packer to top zone and swabbed dry. Acidized from 4138 to 4154 with 500 gallons Reg. NE acid. After treatment the top zone also swabbed water with show of gas. Squeezed all perf. under a cement retainer, drilled retainer and cement to 4150. Sand notched at 4138 and 4140. Acidized with 500 gallons retarded acid. Let acid soak over night. Swabbed well off next day. Started flowing. 5 bbls of water per hour and 37 mcf/day.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>W. K. Byrom</u>	TITLE <u>Geologist</u>	DATE <u>3-7-70</u>
APPROVED BY <u>[Signature]</u>	TITLE <u>[Signature]</u>	DATE <u>MAR 16 1970</u>
CONDITIONS OF APPROVAL, IF ANY:		