Form 3160-3 (December 1990)

UNITED STATES SUBMIT IN TRIP CATE* Form approved. Conserve. A STATES Form approved.

BUREAU OF LAND MANAGEMENT 1625 N. French	CONFIDENTIAL TIGH	T HOLE
	882 10 MNM 104724	SERIAL NO.
AT LIGATION ON LEMMIN TO BRILL ON BELL EN	6.IF INDIAN, ALLOTTEE OR T	RIBE NAME
la TYPE OF WORK: DRILL DEEPEN	7.UNIT AGREEMENT NAME	
b. TYPE OF WELL:	NMNM 103145X	
OIL WELL Other SINGLE ZONE MULTIPLE ZONE 2 NAME OF OPERATOR	8. FARM OR LEASE NAME, WE	ELL NO X + e <
CHESAPEAKE OPERATING, INC. Attn: Janelle McNeely	₩ ₩₩ 945 S€i	en Hivers Un
3. ADDRESS AND TELEPHONE NO.	— 9.API WELL NO.	
P.O. BOX 18496 OKLAHOMA CITY, OK 73154 405-879-9406	30-025 - 36.	DCAT
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface 2,612' FNL & 330' FEL	Yates Teas' Y	
\mathcal{H}	11.SEC.,T.,R.,M.,OR BLOCK AN	ND SURVEY OR AREA
At top proposed prod. zone Same as above 7 7 R-111-P Potash	9-20S-33E	
14.DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE*	12. COUNTY OR PARISH	13. STATE
	Lea	NM
15.DISTANCE FROM PROPOSED 28' FNLL 16.NO. OF ACRES IN LEASE LOCATION TO NEAREST 280.00	17.NO. OF ACI	RES ASSIGNED ELL
PROPERTY OR LEASE LINE, FT (Also to nearest drig, unit line if any)		
18.DISTANCE FROM PROPOSED LOCATION* 19.PROPOSED DEPTH TO NEAREST WELL, DRILLING, COMPLETED,	20.ROTARY O	R CABLE TOOLS*
OR APPLIED FOR, ON THIS LEASE, FT. 3,360	Rotary	
21.ELEVATIONS (Show whether DF, RT, GR, etc.)	22. APPROX. DATE WOR	K WILL START*
3,553' GR at stake Capitan Controlled Water Basin	Upon approval	
23. PROPOSED CASING AND CEMENTING PROGRAM	<u> </u>	
SIZE OF HOLE GRADE, SIZE OF CASING WEIGHT PER FOOT SETTING DE		ITY OF CEMENT
12 ¼" J-55, 8 5/8" 32# 0' – 1,310'	+/- 665 sx	-
7 7/8" J-55, 5 ½" 15.5# 0' - 3,360'	+/- 595 sx C	RCULATE
Attached please find the Surface Use Plan and Drilling Plan as required by Onshore Order No. 1. A final rig layout will be submitted prior to spud once rig is assigned. Please be advised that Chesapeake Operating, Inc. is considered to be the Operator of the above ragrees to be responsible under the terms and conditions of the lease for the operations conducted.	. A generic rig layout is atta mentioned well. Chesapeake upon the lease lands.	ched as Exhibit H.
Bond coverage for this well is provided by Chesapeake Operating, Inc. under their Nationwide B IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present producti proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true ver	APPROVAL SUBJEC GENERAL REQUIRE SPECIAL STIPULAT	MENTS AND LONG. II
J. Mark Lester SIGNED X J. Mark Lester TITLE Sr. Vice President Exploration	DATEX 8/22/02	
*(This space for Federal or State office use)	OPER OGRIE	NO. <u>147/79</u>
PERMIT NO APPROVAL DATE	TE PROPERTY N	
Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease		
thereon. CONDITIONS OF APPROVAL, IF ANY:	EFF. DATE	-1 1 1 2
SOURCE OF THE BOTTEM, SECTION S.		<u> </u>
APPROVED BY 18/11/MUTHY R. SPISAK TITLE ACTING STATE DIK	API NO. <u>30-0</u>	125-36019

See Instructions On Reverse Side

APPROVAL FOR 1 YEAR

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, figitious or fraudulent statements or representations as to any matter within its jurisdiction

BART BELLED

HECENAED

CU., FIDENTIAL - TIGHT HOLE

Lease No. NM 104724

SURFACE USE PLAN Page 1

ONSHORE OIL & GAS ORDER NO. 1 Approval of Operations on Onshore Federal and Indian Oil and Gas Leases

1. EXISTING ROADS

- a. Existing access road to WTU 943 in Section 9-20S-33E will be utilized. See Exhibit A-2.
- b. See Exhibit A-4 for proposed access road.
- c. Location, access and vicinity plats attached hereto. See Exhibits A-1 through A-4.

2. PLANNED ACCESS ROADS

- a. A new access road 443' in length will be built coming off the existing WTU 943 location in a north easterly direction. See Exhibits A-2 and A-4. The road will be built in accordance with guidelines set forth in the BLM Onshore Orders.
- b. No turnouts are expected.
- c. A locking gate will be installed at the site entrance.
- d. Any fences cut will be repaired. Cattle guards will be installed, if needed.
- e. Surface disturbance and vehicular travel will be limited to the approved location and approved access route. Any additional area needed will be approved in advance.
- 3. LOCATION OF EXISTING WELLS WITHIN A 1-MILE RADIUS OF THE PROPOSED LOCATION see Exhibit B.

4. LOCATION OF PRODUCTION FACILITIES

Production facilities will be located adjacent to existing WTU 932 - see Exhibit C.

5. LOCATION AND TYPE OF WATER SUPPLY

Water will be obtained from a private water source. Chesapeake Operating, Inc. will ensure all proper notifications and filings are made with the state.

CUNFIDENTIAL - TIGHT HOLE

Lease No. NM 104724

SURFACE USE PLAN Page 2

6. CONSTRUCTION MATERIALS

It is Chesapeake's understanding, caliche for road building may be obtained from the caliche pit in the NW/4 of Section 9-20S-33E per the BLM. All other material (i.e. shale) will be acquired from private or commercial sources.

7. METHODS FOR HANDLING WASTE DISPOSAL

A closed system will be utilized consisting of above ground steel tanks. All wastes accumulated during drilling operations will be contained in a portable trash cage and removed from location and deposited in an approved sanitary landfill. Sanitary wastes will be contained in a chemical porta-toliet and then hauled to an approved sanitary landfill.

8. ANCILLARY FACILITIES

See Exhibit C for plant facility and Exhibit D for proposed flowlines. The plant facility will be entirely encompassed on an existing location. No new surface disturbance for the plant will be required. The details of the proposed flowlines and additional archeological survey will be submitted under separate sundry notice.

9. WELLSITE LAYOUT

The proposed site layout plat is attached showing rig orientation and equipment location. See Exhibit E.

10. PLANS FOR RECLAMATION OF THE SURFACE

The location will be restored to as near as original condition as possible. Reclamation of the surface shall be done in strict compliance with the existing New Mexico Oil Conservation Division regulations.

Backfilling levelling, and contouring are planned as soon as the drilling rig and steel tanks are removed. Wastes and spoils materials will be buried immediately after drilling is completed. If production is obtained, the unused area will be restored as soon as possible. The rehabilitation will begin after the drilling rig is removed.

11. SURFACE AND MINERAL OWNERSHIP

United States of America
Department of Interior
Bureau of Land Management

CU...FIDENTIAL - TIGHT HOLE

Lease No. NM 104724

SURFACE USE PLAN Page 3

Grazing Lease Held by: Kenneth Smith, Inc. P.O. Box 764 Carlsbad, NM 88220

12. ADDITIONAL INFORMATION

A Class III cultural resource inventory report was prepared by Danny Boone of Boone Archaeological Services, LLC, for the proposed location and new access road. Clearance has been recommended. See Exhibit F.

13. OPERATOR'S REPRESENTATIVES

Drilling and Completion Operations

Colley Andrews District Manager P.O. Box 18496 Oklahoma City, OK 73154 (405) 879-9230 (OFFICE) (405) 850-4336 (MOBILE) (405) 879-7930 (FAX) candrews@chkenergy.com

Production Operations

Dave Wittman 303 E. McAlpine Navasota, TX 77868 (936) 825-3226 (OFFICE) (936) 825-3278 (FAX) (979) 820-3308 (MOBILE) dwittman@chkenergy.com

Drilling Engineer

Keith Curtis P.O. Box 14896 Oklahoma City, OK 73154 (405) 810- (OFFICE) (405) 879-9571 (FAX) (405) 650-6399 (MOBILE) kcurtis@chkenergy.com

Asset Manager

Andrew McCalmont P.O. Box 14896 Oklahoma City, OK 73154-0496 (405) 848-8000 Ext. 852 (OFFICE) (405) 879-7930 (FAX) amccalmont@chkenergy

Regulatory Compliance

Janelle McNeely

Regulatory Compliance Coordinator Mailing Address:

P.O. Box 18496

Oklahoma City, OK 73154

Street Address: 6100 N. Western

Oklahoma City, OK 73118

(405) 879-9406 (OFFICE) (405) 879-7930 (FAX) imcneely@chkenergy.com

CC.. FIDENTIAL - TIGHT HOLE Lease No. NM 104724 SURFACE USE PLAN

Page 4

14. CERTIFICATION

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drill site and access route; that I am familiar with the conditions which presently exist; that the statements made in this surface use plan are. to the best of my knowledge, true and correct; and, that the work associated with the operations proposed will be performed by operator (including contractors and subcontractors) submitting the APD, in conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provisions of 18 U.S.C. 1001 for the filing of a false statement.

By: X 9/22/02

Date: X 8/22/02

CC. FIDENTIAL - TIGHT HOLE Lease Contract No. NM 104724

DRILLING PROGRAM

Page 1

ONSHORE OIL & GAS ORDER NO. 1 Approval of Operations on Onshore Federal and Indian Oil and Gas Leases

All lease and/or unit operations are to be conducted in such a manner that full compliance is made with the applicable laws, regulations (CFR 43, Part 3160) and the approved Application for Permit to Drill. The operator is considered fully responsible for the actions of his subcontractors. A copy of the approved APD must be on location during construction, drilling and completion operations.

Approval of this application does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

1. FORMATION TOPS

The estimated tops of important geologic markers are as follows:

Formation	Depth	Subsea
Rustler	1,300	-2,260
Salt	1,400	-2,160
Base Salt	2,910	-650
Tansill Dolmite	2,950	-610
Yates	3,080	480
Yates Upper 1 Sand	3,085	475
Yates Lower 1 Sand	3,135	425
Yates 2 Carbonate	3,155	405
Yates 2 Sand	3,205	355
Yates 2 Lower Carbonate	3,215	345
Yates 3 U Sand	3,230	330
Yates 3 Middle Sand	3,255	305
Yates 3 Lower Sand	3,290	270
Seven Rivers	3,305	200
Total Depth	3,360	

2. <u>ESTIMATED DEPTH OF WATER, OIL GAS & OTHER MINERAL BEARING FORMATIONS</u>

The estimated depths at which the top and bottom of the anticipated water, oil, gas or other mineral bearing formations are expected to be encountered are as follows:

CC. FIDENTIAL - TIGHT HOLE Lease Contract No. NM 104724

DRILLING PROGRAM

Page 2

Substance	Formation	Depth
Oil	Yates Upper 1 Sand	475
Oil	Yates Lower 1 Sand	425
Oil	Yates 2 Sand	355
Oil	Yates 3 U Sand	330
Oil	Yates 3 Middle Sand	305
Oil	Yates 3 Lower Sand	270

All shows of fresh water and minerals will be reported and protected.

3. BOP EQUIPMENT: 3,000# System

Chesapeake Operating, Inc.'s minimum specifications for pressure control equipment are as follows:

I. BOP, Annular, Choke Manifold, Pressure Test

A. Equipment

- 1. The equipment to be tested includes all of the following that is installed on the well. See Exhibit G.
 - (a) Ram-type and annular preventers,
 - (b) Choke manifolds and valves,
 - (c) Kill lines and valves, and
 - (d) Upper and lower kelly cock valves, inside BOP's and safety valves.

B. Test Frequency

- 1. All tests should be performed with clear water,
 - (a) when installed,
 - (b) before drilling out each casing string,
 - (c) at any time that there is a repair requiring a pressure seal to be broken in the assembly, and
 - (d) at least once every 30 days while drilling.

C. Test Pressure

- 1. In some drilling operations, the pressures to be used for low and high-pressure testing of preventers and casing may be different from those given below due to governmental regulations, or approved local practices.
- 2. If an individual component does not test at the low pressure, **do not**, test to the high pressure and then drop back down to the low pressure.
- 3. All valves located downstream of a valve being tested must be placed in the open position.
- 4. All equipment will be tested with an initial "low pressure" test at 250 psi.
- 5. The subsequent "high pressure" test will be conducted at the rated working pressure of the equipment for all equipment except the annular preventer.

CONFIDENTIAL - TIGHT HOLE Lease Contract No. NM 104724

DRILLING PROGRAM

Page 3

- 6. The "high pressure" test for the annular preventer will be conducted at 70% of the rated working pressure.
- 7. A record of all pressures will be made on a pressure-recording chart.

D. Test Duration

1. In each case, the individual components should be monitored for leaks for <u>5</u> minutes, with no observable pressure decline, once the test pressure as been applied.

II. Accumulator Performance Test

A. Scope

1. The purpose of this test is to check the capabilities of the BOP control systems, and to detect deficiencies in the hydraulic oil volume and recharge time.

B. Test Frequency

1. The accumulator is to be tested each time the BOP's are tested, or any time a major repair is performed.

C. Minimum Requirements

- 1. The accumulator should be of sufficient volume to supply 1.5 times the volume to close and hold all BOP equipment in sequence, without recharging and the pump turned off, and have remaining pressures of 200 PSI above the precharge pressure.
- 2. Minimum precharge pressures for the various accumulator systems per manufacturers recommended specifications are as follows:

System Operating Pressures	Precharge Pressure
1,500 PSI	750 PSI
2,000 PSI	1,000 PSI
3,000 PSI	1,000 PSI

- 3. Closing times for the Hydril should be less than **20 seconds**, and for the ramtype preventers less than **10 seconds**.
- 4. System Recharge time should not exceed **10 minutes**.

D. Test Procedure

- 1. Shut accumulator pumps off and record accumulator pressure.
- 2. In sequence, close the annular and one set of properly sized pipe rams, and open the HCR valve.

CUNFIDENTIAL - TIGHT HOLE Lease Contract No. NM 104724

DRILLING PROGRAM

Page 4

- 3. Record time to close or open each element and the remaining accumulator pressure after each operation.
- 4. Record the remaining accumulator pressure at the end of the test sequence. Per the previous requirement, this pressure **should not be less** than the following pressures:

System Pressure	Remaining Pressure At Conclusion of
	Test
1,500 PSI	950 PSI
2,000 PSI	1,200 PSI
3,000 PSI	1,200 PSI

- 5. Turn the accumulator pumps on and record the recharge time. This time should not exceed **10 minutes.**
- 6. Open annular and ram-type preventers. Close HCR valve.
- 7. Place all 4-way control valves in <u>full open</u> or <u>full closed</u> position. <u>Do not leave in neutral position</u>.

4. CASING AND CEMENTING PROGRAM

a. The proposed casing program will be as follows:

Purpose	Interval	Hole Size	Casing Size	Weight	Grade	Thread	Condition
Surface	0' - 1,310'	12-1/4"	8-5/8"	32	J-55	STC	NEW
Production Liner	0' - 3,360'	7-7/8"	5-1/2"	15.5	J-55	LTC	NEW

- b. Casing design subject to revision based on geologic conditions encountered.
- c. The cementing program will be as follows:

Interval	Туре	Amount	Yield	Washout	Excess
Surface	Lead: 35:65 Poz:Class C + 5% Salt + 6% Gel + 0.1 pps Celloflake Tail: Class C + 2% CC + 0.1 pps Cellofalke	Lead: 470 sx Tail: 195 sx	Lead: 1.94 Tail: 1.34	50%	Lead: 100% Tail: 100%
Production	Lead: Lead: 35:65 Poz:Class C + 5% Salt + 6% Gel + 0.1 pps Celloflake Tail: 50:50 Poz:Class C + 5% Salt + 2% Gel	Lead: 400 sx Tail: 195 sx	Lead: 2.14 Tail: 1.35	20%	Lead: 150% Tail: 50%

CUNFIDENTIAL - TIGHT HOLE Lease Contract No. NM 104724

DRILLING PROGRAM

Page 5

5. MUD PROGRAM

a. The proposed circulating mediums to be used in drilling are as follows:

Interval	Mud Type	Mud Weight	Viscosity	Fluid Loss
0-1,310'	Water Based	8.5-9.3ppg	32-36	NC
1,310'-3,360'	Water based	10.0-10.2ppg	28-30	15-20

A steel pit will be utilized during the drilling of this well. All fluids and cuttings will be disposed of in accordance with New Mexico Oil Conversation Division rules and regulations.

A mud test shall be performed every 24 hours after mudding up to determine, as applicable: density, viscosity, gel strength, filtration, and pH.

6. TESTING, LOGGING AND CORING

The anticipated type and amount of testing, logging and coring are as follows:

- a. Drill stem tests are not planned.
- b. The logging program will consist of GR, Density, Neutron and High Resolution Induction from surface to TD.
- c. Cores samples are not planned.

7. ABNORMAL PRESSURES AND HYDROGEN SULFIDE

- a. The estimated bottom hole pressures is 450 psi. No abnormal pressures or temperatures are anticipated.
- b. Hydrogen sulfide gas is not expected to be encountered.

State of New Mexico

DISTRICT I P.O. Box 1980, Hobbs, NM 88241-1980

Energy, Minerals and Natural Resources Department

Submit to Appropriate District Office State Lease - 4 Copies Fee Lease - 3 Copies

DISTRICT II

P.O. Drawer DD, Artesia, NM 88211-0719

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410

P.O. BOX 2088, SANTA FE, N.M. 87504-2088

API Number

25-

DISTRICT IV

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL LOCATION AND ACREAGE DEDICATION PLAT ☐ AMENDED REPORT Pool Name Pool Code Property Name Well Number

Property Code WTH 945 Operator Name OGRID No. Elevation CHESAPEAKE OPERATING, INC. 3553'

Surface Location


UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
H	9	20-S	33-E		2612	NORTH	330	EAST	LEA

Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
Dedicated Acres	Joint o	r Infill Co	nsolidation	Code Or	der No.				<u> </u>

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED

OR A NON-STANDARD UNIT HAS BEEN APPROVED BY	THE DIVISION
GEODETIC COORDINATE SPC NME NAD 1927 Y=578131.3 X=707303.7 LAT. 32'35'15.31'N LONG. 103'39'37.01'W	I hereby certify that the well location shown



Chesapeake CHESAPEAKE OPERATING, INC.

West Teas Unit
Lea County, New Mexico
Auphotos with well spots


West Teas Auphotos amp.

Chesapeake OPERATING, INC.

WTU 945 Proposed Access Road

CONFIDENTIAL

VICINITY MAP




SCALE: 1" = 2 MILES

SEC. 9 IWP. 20-	S_RGE33-E
SURVEYN.N.	М.Р.М.
COUNTYI	EA
DESCRIPTION 2612'	FNL & 330' FEL
ELEVATION	3553'
OPERATOR_CHESAPE	AKE OPERATING, INC.
LEASE	WTU

JOHN WEST SURVEYING HOBBS, NEW MEXICO (505) 393-3117

Exhibit A-3

LOCATION VERIFICATION MACONFIDENTIAL




SCALE: 1" = 2000'

CONTOUR INTERVAL: 10' LAGUNA GATUNA, N.M.

SEC. 9 TWP. 20-	<u>S_RGE33-E</u>
SURVEYN.M.	и.Р.м
COUNTYL	.EA
DESCRIPTION 2612' I	FNL & 330' FEL
ELEVATION	3553'
OPERATOR CHESAPEAKE OPERATING, INC.	
LEASE	WTU
U.S.G.S. TOPOGRAPHIC MAP LAGUNA GATUNA, N.M.	

JOHN WEST SURVEYING HOBBS, NEW MEXICO (505) 393-3117





West Teos Area Wells within 1 mile of WTU 945

> E/17/07 Seek 104/42/19

Exhibit B

Chesapeake Energy Proposed West Teas Unit Plant 2310' FNL - 2310' FEL SW NE Section 9-T20S-R33E Lea County, NM






CHESAPEAKE
OPERATING, INC.

West Teas Unit
Lea County, New Mexico
Airohotos with well spots

WTU 945 Proposed Flowline



State: 0, Private: 0

CONFIDENTIAL

TITLE PAGE/ABSTRACT/ NEGATIVE SITE REPORT CFO/RFO

1/95 3. NMCRIS No. 80020 2. (ACCEPTED) (REJECTED) 1. BLM Report No. 4. Title of Report (Project Title) 5. Project Date(s) 31 July, 2002 to 16August, 2002 Class III archaeological survey of a pad for the WIII well No. 924 and a pad 6. Report Date 21 August, 2002 and access road for the WTU well No. 945 for Chesapeake Operating, INC in Section 9, T 20S, R 33E, NMPM, Lea County, New Mexico. 8. Permit No. 7. Consultant Name & Address: Direct Charge: Danny Boone 190-2920-02-B Name: Boone Archaeological Services, LLC Address: 2030 N. Canal 9. Consultant Report No. Carlsbad, New Mexico BAS 8-2-05 Authors Name: Danny Boone Field Personnel Names: Danny Boone Phone: (505) 885-1352 10. Sponsor Name and Address: 11. For BLM Use Only. Indiv. Responsible: Janelle McNeely Name: Chesapeake Operating, INC. Address: P.O. Box 18496 12. ACREAGE: Oklahoma City, Oklahoma 73154-7930 Total No. of acres Phone: (405) 848-8000 surveyed: 31.2 (+/-) SURFACE OWNERSHIP: Federal: 31.2 (-/+)

- 13. Location: (Maps Attached if Negative Survey)
 - a. State: New Mexico
 - b. County: Lea
 - c. BLM Office Carlsbad
 - d. Nearest City or Town: Maljamar, New Mexico
 - e. Legal Location: T 20S R 33E Sec.9, WTU No. 924; SE NW, NE SW: WTU No. 945 Pad; SE NE, NE SE, Access Road, NE NE SE, NW NE SE:

Well Footages: WTU No. 924, 2562' FNL, 2210' FWL

WTU No. 945, 2612' FNL, 330' FEL

- f. USGS 7.5 Map Name(s) and Code Number(s): LAGUNA GATUNA, NM (1984) 32103-E6
- g. Area: Block: surveyed: 400' x 400' times 2 pads

Impact: Within survey area of pads [See 14 b.]

Linear: Surveyed: 100' x 443' Impact: 50' x 443'

14. a. Records Scarch; ARMS: Date(s): 15 August, 2002 Name(s): Danny Boone

BLM Office: Date(s): 01 August, 2002

Name(s): Danny Boone

List Sites within .25 miles of Project: Show sites within 500' on Project Map

b. Description of Undertaking:

On 31 July 2002 Danny Boone was at the location to meet with Chesapeake representative Andrew McCalmont but due to a mixup in communication this did not occur. On 01 August, 2002 Danny Boone of Boone Archaeological Services, Don Peterson of the Carlsbad BLM, Chesapeake personnel D. O. Wittman and Andrew McCalmont met in the field and the affected area was superficially examined. Due to environmental concerns a new location for the WTU No. 945 was selected and John West Engineering then proceeded with the staking process.

The WTU well No. 924 will be served by an existing lease road that passes through the north portion of the pad area. The WTU well No. 945 has an access road that begins at the northeast portion of the WTU well No. 943 and trends northeast to a point approximately 50 inside of the southwest portion of the pad survey area. Plats are attached to this report. Total survey acreage is estimation and was arrived at because of the update of LA 59589.

c. Environmental Setting (NRCS soil designation; vegetative community; etc.):

Topography: Transition zone from flat sandy plain to high dunes

Vegetation: 40% (-/+) groundcover, mesquite, sage brush, shin oak, soap berry tree, broom snakewood, assorted sunflowers, various grasses and other flora.

NRCS: Peyote-Maljamar-Kermit association: Gently undulating and rolling, deep, sandy soils

d. Field Methods:

Transect intervals: For the pads, a grid of parallel transects spaced fifteen meters or less and for the road, transects spaced up to 15 meters each side of flagged center line.

Crew Size: One Time in Field: 35 hrs.

15. Cultural Resource Findings:

a. Identification and description

The southeast corner of the WTU No. 924 and the north portion of the WTU No. 945 were in contact with the drawn boundaries of LA 59589 and this site was updated. The original recording of LA 59589 in 1987 recommended inclusion in the National Register of Hisoric Places and stated that the length was 700 meters east to west, an update by the same recorders in 1992 states 700 meters long but on the Topographic Map it had grown to approximately 1650 meters (one mile). Another update in 1995 by another orginazation shows a site approximately 700 meters long. The 1992 update collected a carbon sample and the 1995 update collected a obsidian flake, these samples or the results do not appear in the records beyond this. The 1992 update resulted in the placement of a overhead electric line across LA 59589. The current update resulted in a total redifining of the boundaries of LA 59589 and resulted in the recording of LA 137102 and LA 137103. LA 137102 is recommended for the National Register.

LA 59589 at UTM cordinates 625798E, 3606290N, BLM II site recommended for the National Register.

LA 137102 at UTM cordinaates 624783E, 3606063N, BLM II site recommended for the National Register.

LA 137103 at UTM cordinates 625098E, 3606099N BLM II site not recommended for the National Register.

16. Management Summary (Recommendations):

Archaeological clearance of a pad for the WTU well No. 924 and the pad and access road for the WTU well No. 945 for Chesapeake Operating, INC in Section 9, T 20S, R 33E, NMPM, Lea County, New Mexico as presently staked is recommended provided that two stipulations are followed. A barrier fence be erected on the WTU No. 924 120' southeast of the drill hole across the southeast portion of the pad and no construction be allowed beyond this point; a barrier fence be erected on the WTU No. 945 across the northern portion of the pad 120' north of the drill hole and no construction be allowed beyond this point and a

P:4/9

CONFIDENTIAL

qualified archaeological monitor is prestent during initial surface disturbing activities. See attached diagrams. All activity should cease and the B LM archaeologist be notified immediately if any cultural resources are encountered at any time.

I certify that the information provided above is correct and accurate and meets all appreciable BLM standards.

Responsible Archaeologist

Signature /

8-21-

Date



Pad for the WTU well No. 924 and a pad and access road for the WTU well No. 945 for Chesapeake Operating, INC

Boone Archaeological Services, LLC

Report No.: BAS 8-2-05

NMCRIS No. 80020

Chesapeake Operating, INC. P.O. Box 18496 Oklahoma City, Oklahoma 73154-7930

Attention:

Ms Janelle McNeely

1. Introduction:

An intensive archaeological survey of a pad for the WTU well No. 924 and a pad and access road for the WTU well No. 945 for Chesapeake Operating, INC in Section 9, T 20S, R 33E, NMPM, Lea County, New Mexico. Fieldwork was conducted on 7, 13, 14, & 16 August 2002 and resulted in the update of LA 59589, recording of LA 137102 and LA 137103.

2. Legal Description:

T 20S, R 33E, Sec. 9; WTU No. 924; SF NW, NE SW: 2562' FNL, 2210' FWI.

WTU No. 945, WTU No. 945 Pad; SE NE, NE SE, 2612' FNL, 330' FEL

Access Road, NE NE SE, NW NE SE; 443' in length:

Map Reference, USGS 7.5' Series: LAGUNA GATUNA, NM (1984) 32103-E6

Land Status: BLM, Carlsbad Field Office

Project Description:

On 31 July Danny Boone was at the location to meet with Chesapeake representative Andrew McCalmont but due to a mix-up in communication this did not occur. On 01 August, 2002 Danny Boone of Boone Archaeological Services, Don Peterson of the Carlsbad BLM, Chesapeake personnel D. O. Wittman and Andrew McCalmont met in the field and the affected area was superficially examined. Due to environmental concerns a new location for the WTU No. 945 was selected and John West Engineering then proceeded with the staking process.

The WTU well No. 924 will be served by an existing lease road that passes through the north portion of the pad area. The WTU well No. 945 has an access road that begins at the northeast portion of the WTU well No. 943 and trends northeast to a point approximately 50° inside of the southwest portion of the pad survey area. Plats are attached to this report. Total survey acreage is estimation and was arrived at because of the update of LA 59589.

Topography: Transition zone from flat sandy plain to high dunes

Vegetation: 40% (-/+) groundcover, mesquite, sage brush, shin oak, soap berry tree, broom snakeweed, assorted sunflowers, various grasses and other flora.

NRCS: Simona-Pajaraito association: sandy, deep soils and soils that are shallow to caliche; from wind-worked deposits..



Aspect: 360 degrees

Elevation; Varies from 3550' (+/-)

Lithic Resources: Chert and quartzite occur in the local gravels Water Sources: (potential) No known potable source nearby (permanent) Pecos River approximately 35 miles west.

3. Examination Procedure:

For the pad, a grid of parallel transects spaced fifteen meters or less and for the road, transects spaced up to 15 meters each side of flagged center line.

Area Delineation: Staked by client

Visibility: 15 to 100 % Weather: Clear, sunny, hot Lighting Conditions: Good Work Hours on the Ground: 35

Crew Size: One

4. Findings:

The southeast corner of the WTU No. 924 and the north portion of the WTU No. 945 were in contact with the drawn boundaries of LA 59589 and this site was updated. The original recording of LA 59589 in 1987 recommended inclusion in the National Register of Hisoric Places and stated that the length was 700 meters east to west, an update by the same recorders in 1992 states 700 meters long but on the Topographic Map it had grown to approximately 1650 meters (one mile). Another update in 1995 by another orginazation shows a site approximately 700 meters long. The 1992 update collected a carbon sample and the 1995 update collected a obsidian flake, these samples or the results do not appear in the records beyond this. The 1992 update resulted in the placement of a overhead electric line across LA 59589. The current update resulted in a total redifining of the boundaries of LA 59589 and resulted in the recording of LA 137102 and LA 137103. LA 137102 is recommended for the National Register.


LA 59589 at UTM cordinates 625798E, 3606290N, BLM II site recommended for the National Register.

LA 137102 at UTM cordinaates 624783E, 3606063N, BLM II site recommended for the National Register.

I.A 137103 at UTM cordinates 625098E, 3606099N BLM II site not recommended for the National Register.

Recommendations:

Archaeological clearance of a pad for the WTU well No. 924 and the pad and access road for the WTU well No. 945 for Chesapeake Operating, INC in Section 9, T 20S, R 33E, NMPM, Lea County, New Mexico as presently staked is recommended provided that two stipulations are followed. A barrier fence be erected on the WTU No. 924 120' southeast of the drill hole across the southeast portion of the pad and no construction be allowed beyond this point; a barrier fence be erected on the WTU No. 945 across the northern portion of the pad 120' north of the drill hole and no construction be allowed beyond this point and a qualified archaeological monitor is prestent during initial surface disturbing activities. See attached diagrams. All activity should cease and the B LM archaeologist be notified immediately if any cultural resources are encountered at any time.




Location Map for of a pad for the WTU well No. 924 and a pad and access road for the WTU well No. 945 for Chesapeake Operating, INC in Section 9, T 20S, R 33E, NMPM, Lea County, New Mexico.

Map Reference USGS 7.5' Series: LAGUNA GATUNA, NM (1984) 32103-E6


CONFIDENTIAL


DIAGRAM FOR WTU WELL No. 924





CONFIDENTIAL

DIAGRAM FOR WTU WELL No. 945









C



in reply refer to: 3104 (93200-rayo) Nationwide Bond

United States Department of the Interior

BUREAU OF LAND MANAGEMENT

New Mexico State Office 1474 Rodeo Road P. O. Box 27115 Santa Fe, New Mexico 87502-0115

June 21, 1999

DECISION

Bonded Subsidiaries:

Chesapeake Operating, Inc.

Chesapeake Mid-Continent Corp.

Chesapeake Exploration Limited Partnership

P.O. Box 18496

Oklahoma City, OK 73154

Surety:

Underwriters Indemnity Company Greenway Plaza, Suite 400 Houston, TX 77046 BLM Bond No.: NM2634

Surety Bond No.: B7258

Bond Type: Oil and Gas

Amount of Bond \$150,000.00

Execution Date: 3/20/1998

Rider Accepted

On February 11, 1999, Rider No. 4 was filed to the bond described above. The rider adds Chesapeake Exploration Limited Partnership, as an additional principal. The rider has been examined and found satisfactory and is accepted effective, February 11, 1999, the date filed in this office.

The parent company, Chesapeake Energy Corporation, holds no title to any properties in this name, and is not required to be bonded at this time. Chesapeake Exploration Limited Partnership is a subsidiary of Chesapeake Energy Corporation.

RECEIVED
JUN 2 4 1999
BY: Jw

We specifically call your attention to the fact that the bond described above now provides coverage for Chesapeake Exploration Limited Partnership, either jointly or individually, as long as the ownership remains the same.

If you have any questions, you may contact me at (505) 438-7610.

Is! Rose Ann Ortiz
Rose Ann Ortiz
Land Law Examiner
Fluids Adjudication Team