



NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

OFFICE OF THE COMMISSIONER

WELL RECORD

1961 MAY 1

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES  
LOCATE WELL CORRECTLY

KIRKLIN DRILLING COMPANY

R.B. Farris Kirklín Drilg. Co. Phillips State

(Company or Operator)

(Lease)

Well No. 1, in NE 1/4 of NE 1/4, of Sec. 33, T. 23S, R. 33E, NMPM.  
Wildcat Pool, Lea County.

Well is 660 feet from N line and 660 feet from E line  
of Section 33. If State Land the Oil and Gas Lease No. is E-1932

Drilling Commenced 5/9/61, 19... Drilling was Completed 5/21/61, 19...

Name of Drilling Contractor Company tools P&A 5/22/61

Address Box 3215 Odessa, Texas

Elevation above sea level at Top of Tubing Head 3577.2 GL  
Not, 19... The information given is to be kept confidential until

OIL SANDS OR ZONES

No. 1, from 0 to... No. 4, from... to...  
No. 2, from... to... No. 5, from... to...  
No. 3, from... to... No. 6, from... to...

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rises in hole.

No. 1, from... to... feet.  
No. 2, from... to... feet.  
No. 3, from... to... feet.  
No. 4, from... to... feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8"	24#	N	338'	Baker	Hot		Surface

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. BAGS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11"	8-5/8"	350.73'	200 sk	P&P		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

None Dry and Abd

Result of Production Stimulation

Depth Cleaned Out

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 5265' feet to feet, and from feet to feet.  
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing P&A, 19  
OIL WELL: The production during the first 24 hours was barrels of liquid of which % was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity.  
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.  
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Devonian	T. Ojo Alamo	
T. Salt	T. Silurian	T. Kirtland-Fruitland	
B. Salt	T. Montoya	T. Farmington	
T. Yates	T. Simpson	T. Pictured Cliffs	
T. 7 Rivers	T. McKee	T. Menefee	
T. Queen Del Sd-5072	T. Ellenburger	T. Point Lookout	
T. Grayburg	T. Gr. Wash	T. Mancos	
T. San Andres	T. Granite	T. Dakota	
T. Glorieta	T.	T. Morrison	
T. Drinkard	T.	T. Penn	
T. Tubbs	T.	T.	
T. Abo	T.	T.	
T. Penn	T.	T.	
T. Miss	T.	T.	

FORMATION RECORD 2 elec logs

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	15		Caliche				
15	600		Red Beds				
600	1230		Red rock, shells				
1230	2200		Salt				
2200	3200		Salt & Anhy				
3200	4000		Anhy				
4000	4690		Salt				
4690	5020		Anhy				
5020	5072		Line				
5072	5265	TD	Del Sd				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

5/31/61  
Company or Operator KIRKLIN DRILLING COMPANY Address c/o Oil Reports (Date)  
Name Helen Smith Box 763 Hobbs, N.M.  
Agent