

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-11424.
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

LC 031620

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	NMEU
3. ADDRESS OF OPERATOR	8. FARM OR LEASE NAME
Continental Oil Company	Skaggs B
9. LOCATION OF WELL (Report location clearly and in accordance with any State requirements* See also space 17 below.) At surface	9. WELL NO.
Box 460, Hobbs, N. Mex. 88290	1
10. FIELD AND POOL, OR WILDCAT	10. FIELD AND POOL, OR WILDCAT
660' FNL & 660' FWL, Sec. 12, T-20S	Dr. M. P. V. 7-11
11. PERMIT NO.	11. Sec., T., R., M., OR B.L. AND SURVEY OR AREA
R-37E, Lea county, N. Mex.	Sec. 12, T-20S, R-37E
12. COUNTY OR PARISH	13. STATE
Lea	N. Mex.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

In attempting to pull tubing, it was found that both strings had parted at 6819'. Fished for tubing, and left mud anchor from Glorieta string in hole, and also left tubing below 6819' with Baker model D Packer at 6850' from Drinkard string. Set retrievable bridge plug at 5600', ran 2 3/8 O.D. tubing to 5379'. Placed Glorieta zone on pump, and temporarily abandoned Drinkard zone. Verbal approval was given for this procedure by Mr. A. R. Brown on 9-10-68.

USGS-5 Pan Am-Hobbs 2, All-Rouse 2 Calif-mid 3 file

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Assistant Division Manager

DATE 9-13-68

(This space for Federal or State office use)

APPROVED BY

TITLE

APPROVED DATE

CONDITIONS OF APPROVAL, IF ANY:

SEP 16 1968

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER