## STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

		TITLE
<b>40. 07 E07129</b> SCCC17CB	T	
DISTRIBUTION		
SANTA FE		
FILE	Ī	
U.S.G.S.		
LAND OFFICE		
OPERATOR		

	00. 07 to-140 acceives	OIL CONSERVATION DIVISION	
	DISTRIBUTION	P. O. BOX 2088	Form C-103
	SANTA FE	SANTA FE, NEW MEXICO 87501	Revised 10-1-78
	FILE		Sa Indiana The Allerta
	U.S.G.S.		5a. Indicate Type of Lease
	LAND OFFICE		State Foo X
	OPERATOR		5. State Oil & Gas Lease No.
			-
	SUNI (DO NOT USE THIS FORM FOR USE "APPLIC	DRY NOTICES AND REPORTS ON WELLS PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. ATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
1.			7. Unit Agreement Name
	WELL GAS WELL	Water Injection Well	Skaggs Grayburg Unit
2. N	lame of Operator	NO OCT TIPLE COTAIN METT	8, Farm or Lease Name
	TEXACO Inc.		Skaggs Grayburg Unit
3. A	ddress of Operator		9. Well No.
	P. O. Box 728, Hob	bs, New Mexico 88240	1
4. L	ocation of Well		10. Field and Pool, or Wildcat
	UNIT LETTER K	1985 FEET FROM THE SOUTH LINE AND 1980 FEET FROM	Skaggs Grayburg
		TION 12 TOWNSHIP 20-S RANGE 37-E NMPM.	
111		15. Elevation (Show whether DF, RT, GR, etc.)	12. County
		3569 (DF)	Lea

<b>c.</b>	Check Appropriate B	Box To Indicate	Natu	ire of Notice, Report	t or Other Data	. •	
NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:				
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER		PLUG AND ABANDON	_	EMEDIAL WORK  DAMMENCE DRILLING OPNS.  ISING TEST AND CEMENT JQB  OTHERROPE_1	C Vaterflow	ALTERING CASING  PLUG AND ABANDONMENT	x

- 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.
  - 1. Rigged up. Install BOP. Pull Packer and tubing.
  - Set RBP @ 3016' and spot 4 sx. sand on plug.
  - Perforate 7 5/8" Casing W/1-JS @ 1489'.
  - Set Cement retainer @ 1406'. Cement perforation @ 1489' W/200 sx Class "H" Cement containing 2% CACL. Cement circulated. WOC. DOC. Did not hold.
  - Set cement retainer @ 1374'. Cement perforation @ 1489' W/500 sx. Class "H" Cement containing 3% CACL. WOC. DOC. Did not hold.
  - Set cement retainer @ 1374'. Cement perforation @ 1489' W/400 SX. Class "H" Cement containing 3% CACL and 1,000 gals. Flochex. WOC. DOC.
  - Tested casing to 700# for 30 minutes, 4:00-4:30 PM, 10-18-83. Tested OK.
  - Ran 2 3/8" plastic coated tubing Wokr. and set @ 3634'. Return to injection

5/ · F	- contour castring w/ burn	. and bec @ 1014 .	Recurr to Inj	ecu on.		
	•					
18. I hereby certify that the information ab	ove is true and complete to the be	at of my knowledge and belief	•			
1/01/- 15	,					
		Asst. Dist. Mor.		10-27-83		
SIGNED		Assc. Disc. Mgr.	DATE	10-21-03		
CRIGINAL SIGNED B	Y JERRY SEXTON					
DISTRICT I SU	IPERVISOR			OCT 3 1 1983		
APPROVED BY	TITLE		DATE	001 0 T 1203		
CONDITIONS OF APPROVAL, IF ANY:						

HOBBS OFFICE