

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM-0557686

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. NAME OF OPERATOR
CONTINENTAL OIL COMPANY

3. ADDRESS OF OPERATOR
P.O. BOX 460 HOBBS, NEW MEXICO

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL + 660' FEL SEC. 13

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3556' DF

7. UNIT AGREEMENT NAME
SEMU

8. FARM OR LEASE NAME

SEMU PERMIAN

9. WELL NO.

41

10. FIELD AND POOL, OR WILDCAT

ELEMENT GAS

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC 13, T-20S, R-37E

12. COUNTY OR PARISH

LEA

13. STATE

NEW MEX

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☒

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

IT IS PROPOSED TO PLUG AND ABANDON THE SEMU PERMIAN NO. 41 FOR ECONOMICAL REASONS. THE WELL WILL BE PLUGGED WITH THE FOLLOWING PROCEDURE:

CIBP W/1 SACK CEMENT IS SET AT 3720'. PULL TUBING TO 3380' AND PUMP 50 SACKS CLASS "C" CEMENT, SET SURFACE PLUG W/2 SACKS CEMENT AND SET DRY HOLE MARKER. MUD BETWEEN PLUGS WILL CONTAIN 25 SACKS GEL PER 100 BARRELS.

18. I hereby certify that the foregoing is true and correct

SIGNED

(Signature)

TITLE **ADMINISTRATIVE SUP.**

DATE **6-15-72**

(This space for Federal or State office use)

APPROVED

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

JUN 2 1972

USGS(5) FILE NMFU(3)

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

RECEIVED

JUN 27 1972

OIL CONSERVATION COMM.
HOLDC, R. 11