## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Budget Bureau 42–R358.3. Approval expires 12–31–55.
îga ûru <b>ces</b>
Land Office
13 031620 b
Lease No.
mot
Unit

NOTICE OF INTENTION TO DRILL	· · · · · · · · · · · · · · · · · · ·	SUBSE	QUENT REPORT OF WATER	SHUT-OFF	
NOTICE OF INTENTION TO DRILL	A NIC	SUBSEC	QUENT REPORT OF SHOOTI		
NOTICE OF INTENTION TO CHANGE PLAN NOTICE OF INTENTION TO TEST WATER		1 1	QUENT REPORT OF ALTERI		
NOTICE OF INTENTION TO RE-DRILL O			QUENT REPORT OF RE-DRI		
NOTICE OF INTENTION TO RE-DRILL O NOTICE OF INTENTION TO SHOOT OR A			QUENT REPORT OF ABANDO		
NOTICE OF INTENTION TO SHOOT OR AL		1 11	EMENTARY WELL HISTORY		
NOTICE OF INTENTION TO ABANDON W					
(INDICAT	E ABOVE BY CHECK N		REPORT, NOTICE, OR OTHER		K).
101-Slagge B-14 No. 3		Hobbs,	Naw Mexico,	Fone 10	, 19
<del></del>	****				
ell No. 3 is locate	ed <b>980</b> ft. f	rom lin	e andtt. tr	om W line of	sec
HE/4 Section 14	208	<b>37%</b>	N. I. P. H. (Meridian)	·	
(1/2 Bec. and Bec. No.)	(1 WP.)	(Range)	(Meridian)	ion Mexico	
Skept (Field)	(Cor	Pts		(State or Territory)	
he elevation of the derrick	floor above sea	a level is	ft. WORK	,	ling jobs, cemen
he elevation of the derrick	floor above set	TAILS OF	MORK  and lengths of proposed count proposed work)	asings; indicate mudd	location '
The elevation of the derrick  State names of and expected depths to  It is intended total depth of appro-	floor above ser  DE  objective sands; sho ing points, and  to drill a variately 37 of the U. S	TAILS OF	work and lengths of proposed coant proposed work) retery tools at	the above	location ecoorden
The elevation of the derrick  State names of and expected depths to  It is intended to total depth of approved asthods  arts will be complied	floor above ser  DE  objective sands; she ing points, and to drill a variantely 33 of the U. S	TAILS OF  ow sizes, weights, d all other import  and the colories  Geologic	ft.  WORK  and lengths of proposed creamt proposed work)  rotary tools at earling will be all Survey and a	the above comented in	location accorden icial req
The elevation of the derrick  State names of and expected depths to  It is intended a total depth of approved methods  ents will be complied	floor above ser  DE  objective sands; she ing points, and  to drill a variately 39 of the U. S	TAILS OF  TAILS	ft.  WORK  and lengths of proposed count proposed work)  rotary tools at oacing will be all Survey and a	the above comented in any other sp	location encorden  cial req  ing to be
The elevation of the derrick state names of and expected depths to total depth of approved methods and a mill be complied.	floor above ser  DE  objective sands; she ing points, and  to drill a variately 37 of the U. S  with.	TAILS OF ow sizes, weights, dall other import well with OO'. All . Geologic	ft.  WORK  and lengths of proposed country tools at earling will be all Survey and a leading patterns	the above comented in any other spi	location accorden acial req ing to be t, cement
The elevation of the derrick state names of and expected depths to total depth of approved methods will be complied at approximately 250°	floor above ser  DE  objective sands; she ing points, and  to drill a variantely 37 of the U. S  with.  o use the f	TAILS OF ow sizes, weights, d all other import well with OO'. All . Geologic collowing of	ft.  WORK  and lengths of proposed control proposed work)  rotary tools at eating will be all Survey and a sering patterns roximately 250	the above comented in any other spinsted spinste	location assorder actal req irig to be t, cement
The elevation of the derrick  State names of and expected depths to  It is intended a total depth of approximate will be complied  It is planted to surface circulated to surface.	floor above ser  DE  objective sands; sho ing points, and to drill a variable 33 of the U. S  ivith.  o use the f and occurred and occurred and occurred	TAILS OF  TAILS  TAILS OF  TAILS  TA	ft.  WORK  and lengths of proposed createry tools at easing will be said Survey and a sering patterns proximately 250 be set at apprent.	the above comented in any other spins sacks comented to be de	location assorder actal req irig to be t, cement
he elevation of the derrick  It is intended to total depth of approved methods will be complied  It is planned to approximately 250° or circulated to surfacemented with approximately casing aligner survey. Casing	floor above ser  DE  objective sands; she ing points, and  to drill a  minately 39 of the U. S  with.  to use the f and commute  ser; 5 1/20  nately 1,150  ng to be per	TAILS OF  TAILS	ft.  WORK  and lengths of proposed count proposed work)  rotary tools at easing will be sain such as a sain suc	the above comented in any other spons sacks coment to be described.	location encordent required to be to open to be to open to be to open to be to open to
he elevation of the derrick  It is intended  It is intended  It total depth of approximate will be complied  It is planned to surface circulated to surface will approximately 250°	floor above ser  DE  objective sands; she ing points, and  to drill a  minately 39 of the U. S  with.  to use the f and commute  ser; 5 1/20  nately 1,150  ng to be per	TAILS OF  TAILS	ft.  WORK  and lengths of proposed count proposed work)  rotary tools at easing will be sain such as a sain suc	the above comented in any other spons sacks coment to be described.	location encordent required to be to open to be to open to be to open to be to open to
It is intended to total depth of approval to surface and expected depths to its approved methods and with approximately 250° correlated to surface anished with approximately 250° correlated with approximation of the planes. Casin Approval to pro-	floor above ser  DE  objective sands; she ing points, and to drill a variable 33 of the U. S  with.  to use the f and commute ser; 5 1/20 nately 1,150 ng to be par	TAILS OF  TAILS  TAILS OF  TAILS  TA	work  and lengths of proposed createry tools at caning will be all Survey and a mesing patterns proximately 250 be set at apprent, exact amo posite the pay	the above comented in any other spins sacks coment to be described by the spins to be described by the	location encordent required to be to commit 900° and terminad
he elevation of the derrick  tate names of and expected depths to  It is intended in total depth of approved methods  at approved methods  It is planned to approximately 250° on circulated to surfacemented with approximation and approximation of the proval to prove the condensate of the cond	floor above ser  DE  objective sands; sho ing points, and to drill a laminately 33 of the U. S  with.  so use the f and comente and comente and comente and to be per odnoo this a  k must receive appro-	TAILS OF  ow sizes, weights, d all other import  well with  OO'. All  Geologic  collowing of d with app  casing to sacks con forgted of  well upon  ovalin writing by	work  and lengths of proposed createry tools at caning will be all Survey and a mesing patterns proximately 250 be set at apprent, exact amo posite the pay	the above comented in any other spins sacks coment to be described by the spins to be described by the	location encordent required to be to commit 900° and terminad
It is intensed to total depth of approved acthods will be complied at approved acthods at approximately 250° or circulated to surfacemented with approximately 250° or circulated with approximately 250° or circulated with a possible circulated with approximately 250° or circulated with a possible circulated with a po	floor above ser  DE  objective sands; sho ing points, and to drill a laminately 33 of the U. S  with.  so use the f and comente and comente and comente and to be per odnoo this a  k must receive appro-	TAILS OF  ow sizes, weights, d all other import  well with  OO'. All  Geologic  collowing of d with app  casing to sacks con forgted of  well upon  ovalin writing by	work  and lengths of proposed createry tools at caning will be all Survey and a mesing patterns proximately 250 be set at apprent, exact amo posite the pay	the above comented in any other spins sacks coment to be described by the spins to be described by the	location encordent required to be to commit 900° and terminad
It is intended to take a supervised by the complied of approximately 250° to approximate	floor above ser  DE  objective sands; she ing points, and  to drill a variantely 37 of the U. S  with.  to use the f and ownerte  see; 5 1/25  mately 1,150  of to be per  odnes this a  k must receive appro-	TAILS OF  ow sizes, weights, d all other import  well with  OO'. All  Geologic  collowing of d with app  casing to sacks con forgted of  well upon  ovalin writing by	ft.  WORK  and lengths of proposed crant proposed work)  rotary tools at easing will be all Survey and a sessing patterns proximately 250 be set at appropriate the pay completion is a the Geological Survey before the Geological Survey before the completion of the	the above comented in any other spins sacks coment to be described by the spins to be described by the	ing to be to commenced.

te de la compania de la co

A CONTRACTOR OF THE PROPERTY O

n meddiend einede ers en electropment tode den ellig ellige et enterellige et enterellige et ellige enterellige ellige enterellige enterel

The configuration of the confi

The state of the s

· 有性轉移 小鼠的 數 独为康熙节

For the profession of the con-

والمرابع والمتاري والمتعاصف والمتعارب والمتعارب