

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

LC031621B

6. If Indian, Allotment or Tribal Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Britt B no. 3

9. API Well No.

30-025-06102

10. Field and Pool, or Exploratory Area

Eumont Yates-SR-QN

11. County or Parish, State

Lea County N.M

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Conoco Inc.

3. Address and Telephone No.

10 Desta Dr. St. 100w Midland Tx.

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL& 330' FWL (UNIT LETTER) L

SECTION 15, T-205, R-37E

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Tag Cibp. at 3340' Circ. hole w/Gelled Brine Mud.  
2. Spot plug #1 from 3340' to 3090' (25sx.) class C.  
3. Perforated 5-1/2 csg. at 1290' pressed up to 1000# would-not break down.  
4. Spot plug #2 (25sx.) from 1348' to 1160' \*  
5. Perforated 5-1/2 csg. at 300' pumped 30 bbls. down 5-1/2 would-not circ.  
6. Pumped 30sx. down 5-1/2&7-5/8 to 350' rih/ with tbg. to 360' circ. 40sx. to surf. \*  
7. cut off well-head installed dry hole marker.

(1-1400)

\* Approved by Marlan Deaton

Approved as to plugging of this well by  
L. H. Deaton and is retained until  
surface plug is completed.

14. I hereby certify that the foregoing is true and correct

Signed Ben Fisher

Title Field-Supervisor

Date 01/17/00

(This space for Federal or State office use)

(ORIG. SGD) DAVID R. GLASS

Title PETROLEUM ENGINEER

Date MAR 24 2000

Approved by  
Conditions of approval, if any:

BUREAU OF LAND MANAGEMENT  
ROSWELL OFFICE

22 MAR 24 A 10:10

RECEIVED

22 MAR 24  
10:10 AM  
1954