

LOG OF OIL OR GAS WELL

LOCATE WELL CORRECTLY

A blank 10x10 grid for graphing, consisting of 10 columns and 10 rows of squares.

Date April 24, 1938
 Title District Superintendent
 Signed *[Signature]*
 The information given herewith is a complete and correct record of the well and all work done thereon
 as far as can be determined from all available records.
 Location (N) of a line and 1500 ft. of a line of sec. 15
 Well No. 5 Sec 15 T 20 R 24 Meridian
 Lessor or Tract H.A. Britt 2-15
 Field Comment
 Address Box 60, Hobbs, New Mexico
 State New Mexico

Commenced drilling 7-20-39 19 _____ Finished drilling 4-10-39 19 _____

OIL OR GAS SANDS OR ZONES

(D) Das ist es

No. 1 from	to	5485	No. 4 from	to	8885
No. 2 from	to		No. 5 from	to	
No. 3 from	to		No. 6 from	to	

IMPORTANT WATER SANDS

No. 2 from	to	No. 3 from	to
No. 3 from	to	No. 4 from	to

CASING RECORD

[illegible]

It is of the greatest importance to have a complete history of the well. Please state in detail the dates of redrilling, together with the reasons for the work and the results. All there were and all things made in the casing, state pipe, and in any casing was checked out left in the well, giving size and location. If the well has been cased, give date, size, position, and number of shoes. If pipes or bridges were put in to rest for water, state kind of material used, position, and results of pumping or bailing.

HISTORY OF OIL OR GAS WELL

MUDDING AND CEMENTING RECORD

Rating	White set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
4-6/4	383	383	Rotation		
7-6/8	484	484			
8-1/2	484	484			

PLUGS AND ADAPTERS

Blanking plug—Material	Length	Depth set
Adaptor—Material	Size	

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out

all are nearest shot now realized

TOOLS USED

[illegible]

DATE

It was well cut per 24 hours	834,000	% sediment	
.....		% water; and	
The production for the first 24 hours was 1008			
barrels of fluid of which 100 % was oil, %			
Put to producing		Gravity, B6.	
.....			

EMPLOYEES

Driller	Driller	May 1, 1939.
Driller	Driller	

ПОИТАМЯТО

Total depth 3858'. Time pay 3843 to 3858'. 2" tubing set at 3821; initial production 42 bbls oil or hour w/ 824 MCF gas thru

FROM	TO	TOTAL FEET	FORMATION
0	123		Caliche & redbed
133	254		Redbed
254	761		Redbed & shells
761	1070		Redrock
1070	1192		Redrock
1192	1287		anhydrite
1287	1683		anhydrite & salt
1683	1950		Salt & shells
1950	2197		Salt, anhydrite & potash
2197	2440		anhydrite & salt
2440	2593		anhydrite
2593	2783		anhydrite & lime
2783	2828		anhydrite
2828	2997		anhydrite & lime
2997	3035		lime
3035	3118		anhydrite & lime
3118	3172		lime
3172	3203		anhydrite & lime
3203	3335		lime
3335	3366		lime & anhydrite
3366	3858		lime