

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

CONOCO INC.

3. Address and Telephone No.

10 DESTA DRIVE, STE 100 W, MIDLAND, TX 79705 (915) 686-5494

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980 FNL+1980 FWL, Section F, Sect. 15, T20S, R37E

5. Lease Designation and Serial No.

LC-031621B

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Britt B No. 10

9. API Well No.

30-025-06109

10. Field and Pool, or Exploratory Area

Cass Penn

11. County or Parish, State

Lea, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Rodpart - dichlor
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple-completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

6-6-91 Top tbg joint crimped in slip area. Replaced to WH flange w/6" 900x2 7/8" tapered flange. Acidized as follows: pumpd 100 BBLS wtr w/2% KCL + KS-SOL, pumpd 1500 gals 15% HCl-2NE-2FE acid, 3 BBLS spacer, 100 BBLS 0.2% DI-CHLOR-5, 3 BBL spacer, 1500 gals 15% HCl-2NE-2FE acid + flush w/75 BBLS down tbg & 75 BBLS down csg. Tagged fluid at 7600 FS. R/H w/swab, tagged fluid 7300 FS. Made 2 swab run. returned at 5 BBLS total w/150% oil cut. Top jt of tbg crimped at WH slip area. Replace slip type WH flange w/6" x 2 7/8" tapered flange, replaced top jt of 2 7/8" tbg. R/H w/1 1/2" x 10 dip tube, 2 1/2" x 1 1/2" x 20-3 RWBC pump, 2 1/2" K-Bars, 2 1/4" - 7/8" 97 rods & 92-1" non 97 rods. Spaced-out, loaded tbg & set points on pump off controller. Rel Permian unit.

LS

14. I hereby certify that the foregoing is true and correct

Signed

Christine L. Neff

Title

ADMIN. ASSISTANT

Date

9-16-91

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: