

## NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

## WELL RECORD - 47

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

If State Land submit 6 Copies

LOCA	AREA 640 ACE TE WELL COR	res Rectly					
Con	tinental	Oil Compa (Company or Opera	ny Marie	********************************	Br	itt B-15	
							r37. <b>Е</b> , NМРМ
Mor	umant-Tu	bb	*******************************	Pool,La	<b>a</b>		County
/ell is6	60	feet from	South	line and	1980	feet from	
Section	15	If St	ate Land the Oil as	nd Gas Lease No.	<b>i</b>	94 204000 20000 2000 2000 2000 2000 2000	
rilling Com	menced	Sept. 23	•	19	was Completed	Oct. 31,	, 19 60
ame of Dri	lling Contrac	tor Lows	Drilling Co	mpany, Inc.		p4<16+0001+0001+001+0+++++++++++++++++++++	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
ddress		Midl	and, Texas	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			***************************************
levation abo	we sea level s	at Top of Tubing	; Head35	64	The in	formation given is	to be kept confidential unt
			, 19				
			OI	L SANDS OR ZO	)NES		
lo. 1, from	6450	tc	6510	No. 4,	from	***************************************	.to
lo. 2, from	5680	to	5810	No. 5,	from		to
lo. 3, from	5230	to	5310	No. 6,	from		to
			775700		G A NEW		
nclude data	on rate of w	rater inflow and	elevation to which	RTANT WATER water rose in hole			
						feet	
•							
•							•••••
•							
10. 1, 110m	•••••						
				CASING RECO		1	<del></del>
SIZE	WEIGI PER FO			KIND OF SHOE	CUT AND PULLED FROM	PERFORATION	ns Purpose
3 3/8"	48	New	334 1	Lerkin Gu			
9 5/8" _	36	New New	7026	)		k float cal	Lar
<i></i>	20 & 3	23 New	/0/28				
					DEGADO		
				AND CEMENT	ING RECORD		ANALYS OF
SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED		MUD GRAVITY	AMOUNT OF MUD USED
16	13 3/8	340	1,25	Pump & Plu	- U		
12 1/4	9 5/8	4000 6951	<u>1195</u> 380	11 11 11 11 11 11 11 11 11 11 11 11 11			
		97.7.					
			RECORD OF	PRODUCTION A	ND STIMULA	TION	
		(Record t	he Process used, N	o. of Ots. or Gal	s. used, interval	treated or shot.)	
Wall o	was not	•					
							t.of.perfs.
(64,54,	60,6482	-88 <sub>3</sub> 6504+	11)				***************************************
•••••							
Result of Pr	oduction Stin	nulation		***************************************	***************************************		
			**********************	************			
						Depth Cleans	ed Out

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or dexiation surveys were made, submit report a separate sheet and attach hereto

## TOOLS USED

										fcet.	
Cable tools	were use	d from		feet to		feet, an	d from	************	feet to	fcet.	
					PRODU	CTION				•	
Put to Pro	ducing	12-25			, 19 <b>60</b>						
OIL WEI	L: The	production	during the first	24 hours	was	04	b <b>ar</b>	rels of liq	uid of which	% was	
•	was	oil;	%	was emu	ılsion;	2	% water	; and	0	was sediment. A.P.I.	
	Gra	vity <b>36</b>	.90	**********							
GAS WEI		•					A.C.F. pl	US		barrels of	
OAS WEE		_	arbon. Shut in Pr				-, · <b>.</b> .				
	-										
_					4						
PLEA	ASE IND	ICATE B	ELOW FORMA Southeastern			FORMAN	E WITI	1 GEOGI	EOGRAPHICAL SECTION OF STATE):  Northwestern New Mexico		
T. Anhy	1	198	Southenstern					т.	Ojo Alamo		
	1		•••••	<b>T</b> . 8	Silurian			Т.	Kirtland-Fruitland		
B. Salt	2	470 41#		. <i>4</i> 7. 1	Montoya			Т.			
T. Yates			***************************************		Simpson						
	3	100	***************************************		McKee Ellenburger						
T. Quee T. Grayl				<b>T</b> , ! <b>T</b> . (	Ellenburger Gr. Wash						
•					Granite			1			
T. Glorie				Т.				т.			
T. Drink	707 M	647 325	***************************************		**						
	6	ØF 0		:							
		•••••									
					FORMATIC	ON RECC	RD			V.	
From	То	Thickness in Feet	1	Formation	1	From	То	Thickness in Feet		Formation	
0	1198	1196	Redbeds							· ·	
1198	1290	92	Ankydrite							. '	
1290 2470	2470 2618	1180	Salt Dolomite								
2618	4000	1382	Dolamite,	Sanda	tone						
4000 4650	4650 5000	650 350	Delomite Idmestone						, .		
5000	5340	140	Linestone	Dola	mite						
5140	5260	120	Dolamite,								
5260 5550	5550 5800	290 250	Dolomite.	Sanda	tone			1			
5800	6320	520	Dolomite				,	İ			
6320 6430	6430	110	Dolanite,								
9470	6952	522	Delomite,	TATAMA.	Come						
					<u> </u>						
•	•		ATTACH S	EPARA	TE SHEET I	F ADDITIO	NAL SF	PACE IS	NEEDED		

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator.

Company

Company

Address. Box 4.27, Hobbs, New Nexteo

V. G. Kcalister

Position of Title District Superintendent