

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR
CONOCO INC.

3. ADDRESS OF OPERATOR
P.O. Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 660' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☒
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐

(other) mill pkrs, open add'l. pay, acidize

5. LEASE

LC-031621(b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

NMFU

8. FARM OR LEASE NAME

Britt B

9. WELL NO.

12

10. FIELD OR WILDCAT NAME

Weir Blinberry & Monument Tubb

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 15, T-20S, R-37E

12. COUNTY OR PARISH

Lea

13. STATE

NM

14. API NO.

30-025-06111

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU. CO to 6360'. Mill 2 pkrs @ 6360' & 6472'. CO to 6600'. Spot 11 bbls. 15% HCL-NE-FE from 6586' - 6324'. Perf Tubb w/1 JSPP at 6324', 29', 34', 40', 46', 51', 61', 68', 84', 88', 92', 6404', 08', 12', 16', 6558', 67', 74', 81' & 6586' for total of 20 holes. Set pkr @ 6150'. Acidize Tubb perfs in 3 equal stages w/ total of 120 bbls. 15% HCL-NE-FE & 350 lbs. diverting agent. Flush w/53 bbls 2% KCL TFW. Chemucally inhibit Tubb perfs. Rel pkr @ 6150'. Spot 9 bbls. 15% HCL-NE-FE for (cont'd - on next page)

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *W. A. Deiterfeld*

Administrative Supervisor

DATE 12/26/84

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY

SWD

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

DEC 31 1984

Carlsbad

NEW MEXICO

*See Instructions on Reverse Side

RECEIVED

JAN -2 1985

O.C.D.
HOBBS OFFICE