

Amerada Hess Corporation

Form C-105 Attachment – State “Q” Well No. 1 – API No. 30-025-06116

ITEM 26: PERFORATION RECORD

Perf. w/3-1/8” csg. gun w/2 SPF at following: Paddock Zone – 5132’-5137’;
G/SA Zone - 3615’-3618’, 3621’-3624’, 3631’-3634’, 3640’-3645’, 3660’-3664’, 3676’-3679’,
3682’-3686’, 3707’-3711’, 3731’-3735’, 3741’-3746’, 3750’-3770’, & fr. 3772’-3785’;
Eumont Yates 7RQ Zone – 2530’-2532’, 2537’-2539’, 2544’-2546’, 2560’-2562’, 2578’-2580’,
2587’-2590’, 2638’-2640’, 2653’-2655’, 2658’-2661’, 2681’-2683’, 2702’-2705’, 2712’-2716’,
2734’-2737’, 2747’-2783’, 2787’-2789’, 2791’-2792’, 2810’-2812’, 2814’-2818’, 2898’-2900’,
3117’-3119’, 3254’-3258’, 3310’-3313’, 3333’-3337’, 3342’-3344’, 3364’-3373’, 3376’-3384’,
3398’-3412’, 3426’-3431’, 3440’-3442’, & fr. 3454’-3456’.

ITEM 27: ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

5132’-5137’	Acidized Paddock Zone w/250 gal. 15% HCL acid.
3615’-3785’	Acidized G/SA Zone w/3250 gal. 15% HCL acid.
3117’-3456’	Acidized Eumont Zone w/3000 gal. 15% HCL acid.
2530’-2900’	Acidized Eumont Zone w/2500 gal. 15% HCL acid.