

FIELD Mormont Padlock	OPERATOR American Hess Corp	DATE 4-29-76
LEASE State Q	WELL NE LOCATION 1980 FSL-2310 FEL, Sect 16, T-20S, R-37E	

12 1/2" casing set at 172' with 200 sx of El Toro cement
Hole size 17 1/2" Cement e Surface by Calc

8 5/8" casing set at 2444' with 600 sx of Trinity cement
Hole size 11" Top Cement e 400' by Survey

6 5/8" csg. perf'd at 3750-3770' (Squeezed perfs at 3750-70' w/150'sx.
class C cement w/ 37 millicuries of RAC II)

3772' Liner top

6 5/8" casing set at 3776' with 100 sx of El Toro cement
Hole size 7 7/8" Cal. cement 3067'
** 4 1/2" liner perf'd at 5130-5160' (Squeezed perfs at 5130-60' w/100 sx class C cement)
4 1/2" liner perf'd at 5155-5190'
Cast Iron Bridge Plug at 5300'
Baker Model 'DA' Packer at 6425'
4 1/2" liner perf'd at 6455-6566'
4 1/2" liner perf'd at 6652-6675' (Squeezed perfs at 6652-75' w/50 sx reg cement)

4 1/2" liner set at 6775' with 200 sx of _____ cement
Total Depth 6938' Hole size 5 7/8" Cal. cement top 5093'

* 200sx reg. cement mixed w/ 39% LWL

** 7 7/8" Tbs at 4912'

TR 1010