## N ' MEXICO OIL CONSERVATION C MMISSION

Santa Fe, New Mexico

## **MISCELLANEOUS NOTICES**

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be of the Commission.

Indicate nature of	notice by cr	below:			
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	X NO	TICE OF INTENTIC CHEMICALLY TRE	ON TO SHOOT	OR	)
NOTICE OF INTENTION TO CHANGE PLANS		CHESICALLI TRE	N TO PULL O	R	-
NOTICE OF INTENTION TO REPAIR WELL		TICE OF INTENTIC	R CASING	<u>-</u>	
NOTICE OF INTENTION TO DEEPEN WELL			10 110G W	ELL .	
Monument, New M	ferion		7	3000	<u> </u>
		tee	June 5,	1937 Date	
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico.					
Gentlemen:					
Following is a notice of intention to do certain work as	described b	Now at the			
Amanu Bu Dukuus andara	State "2"			200rJ.	<b>cm</b> 1
Company or Operator	Lease	Well No	1	in NW	364 4
	_, N. M. P.	M., Monu	ment		Field
County.					
FOLLOW INSTRUCTIONS IN THE RULE -5/8" 20# 10-Thd. New Seamless casing the Halliberton Method with 100 sacks.				nd <b>ce</b> me	n <b>t</b> ed
-5/8" 20# 10-Thd. New Seamless casing he Halliberton Method with 100 sacks.  asing and fittings will be tested with maisturbed for thirty minutes. If no disturbed out of the casing and the same oplied and allowed to stand undisturbed	was set in 1200# pur rop in present of for this	n this well a	at 3779° and allowed ta the ceme	to sta	nd 1 <b>t</b> hei
3-5/8" 20# 10-Thd. New Seamless casing the Halliberton Method with 100 sacks.  asing and fittings will be tested with indisturbed for thirty minutes. If no die drilled out of the casing and the same pplied and allowed to stand undisturbed	was set in 1200# pur rop in present of for this	n this well a	at 3779° and allowed ta the ceme	to sta	nd 1 <b>t</b> her
-5/8" 20# 10-Thd. New Seamless casing he Halliberton Method with 100 sacks.  asing and fittings will be tested with maisturbed for thirty minutes. If no disturbed out of the casing and the same oplied and allowed to stand undisturbed	was set in 1200# pur rop in present of for this	n this well a	at 3779° and allowed ta the ceme	to sta	nd l then in be
-5/8" 20# 10-Thd. New Seamless casing he Halliberton Method with 100 sacks.  asing and fittings will be tested with maisturbed for thirty minutes. If no disturbed out of the casing and the same oplied and allowed to stand undisturbed	was set in 1200# pur rop in present of for this	n this well a	at 3779° and allowed ta the ceme	to sta	nd l then in be
-5/8" 20# 10-Thd. New Seamless casing he Halliberton Method with 100 sacks.  asing and fittings will be tested with indisturbed for thirty minutes. If no die drilled out of the casing and the same pplied and allowed to stand undisturbed	was set in 1200# pur rop in present of for this	n this well a	at 3779° and allowed ta the ceme	to sta	nd l then in be
-5/8" 20# 10-Thd. New Seamless casing the Halliberton Method with 100 sacks.  asing and fittings will be tested with indisturbed for thirty minutes. If no disturbed out of the casing and the same oplied and allowed to stand undisturbed	was set in 1200# pur rop in present of for this	n this well a	at 3779° and allowed ta the ceme	to sta	nd l the in be
-5/8" 20# 10-Thd. New Seamless casing the Halliberton Method with 100 sacks.  asing and fittings will be tested with indisturbed for thirty minutes. If no distributed out of the casing and the same oplied and allowed to stand undisturbed esults the drilling will then be resumed.	was set in 1200# pur rop in present of for this	n this well a	at 3779° and allowed ta the ceme	to sta	nd l the in be
he Halliberton Method with 100 sacks.  asing and fittings will be tested with indisturbed for thirty minutes. If no destribed out of the casing and the same oplied and allowed to stand undisturbed esults the drilling will then be resumed proved.  JUN 7 1937	was set in 1200# punt rop in present of for third.	n this well appressur are saure result 1200# pump pump ty minutes.	at 3779' and allowed to the cemeroscure will no drop	to sta	nd l then in be
he Halliberton Method with 100 sacks.  asing and fittings will be tested with indisturbed for thirty minutes. If no described out of the casing and the same pplied and allowed to stand undisturbed esults the drilling will then be resumed.	was set in the set of	n this well appressur are saure result 1200# pump pump ty minutes.	at 3779' and allowed ts the cemeroressure will no drop	to sta	nd l then in be
ine Halliberton Method with 100 sacks.  Assing and fittings will be tested with indisturbed for thirty minutes. If no die drilled out of the casing and the same pplied and allowed to stand undisturbed esults the drilling will then be resumed.	was set in 1200# punt rop in present of for third.	n this well appressur are saure result 1200# pump pump ty minutes.	at 3779' and allowed to the cemeroscure will no drop	to sta	nd l ther in be
3-5/8" 20# 10-Thd. New Seamless casing the Halliberton Method with 100 sacks.  Sasing and fittings will be tested with indisturbed for thirty minutes. If no die drilled out of the casing and the same pplied and allowed to stand undisturbed esults the drilling will then be resumed.	was set in the set of	n this well appressur are saure result 1200# pump ty minutes.  Prada Petrols Compan  Ye Court	at 3779' and allowed to the come pressure will no drop	to sta ent wil ill aga p in pr	nd l ther in be
3-5/8" 20# 10-Thd. New Seamless casing the Halliberton Method with 100 sacks.  Sasing and fittings will be tested with indisturbed for thirty minutes. If no die drilled out of the casing and the same pplied and allowed to stand undisturbed esults the drilling will then be resumed.	was set in the set of	p pressur are sure resulting pump ty minutes.  Perada Petrole Compan	at 3779' and allowed to the come pressure will no drop	to sta ent wil ill aga p in pr	nd l ther in be
3-5/8" 20# 10-Thd. New Seamless casing the Halliberton Method with 100 sacks.  Sasing and fittings will be tested with indisturbed for thirty minutes. If no dies drilled out of the casing and the same pplied and allowed to stand undisturbed results the drilling will then be resumed opposed.  JUN 7 1937 1937 1937 1937 1937 1937 1937 19	was set in the set of	p pressur aressure resulting pressure resulting pump pressure resulting resulting pump pressure resulting	at 3779' and allowed to the come pressure will no drop	to sta ent wil ill aga p in pr	nd 1 <b>t</b> her
3-5/8" 30# 10-Thd. New Seamless casing the Halliberton Method with 100 sacks.  Sasing and fittings will be tested with indisturbed for thirty minutes. If no die drilled out of the casing and the same pplied and allowed to stand undisturbed esults the drilling will then be resumed approved.  JUN 7 1937 1937 19	Was set in 1200# pum rop in present of for thir in a set of for thir in	p pressur aresulting pressure resulting pump pressure resulting resulting pump pressure resulting pump pressure resulting	at 3779' and allowed to the come pressure will no drop the come of	to sta ent wil ill aga p in pr	nd l ther in be

Section 1 Section 2

The state of the state of

. • 10 mm - 10 mm

var i var

. . . . .

The second of the second of the  $\mathbf{e}^{(i)} = \mathbf{e}^{(i)} + \mathbf{e}^{(i)} = \mathbf{e}^{(i)}$