

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-105
Revised 1-1-89

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL APN NO.
30-025-06117
5. Indicate Type of Lease:
STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
B-1469

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:	OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER _____	7. Lease Name or Unit Agreement Name
b. Type of Completion:	NEW WELL ☐ WORK OVER ☒ DEEPEN ☐ PLUG BACK ☒ DEEP RESVR ☐ OTHER _____	State "Q"
2. Name of Operator	Amerada Hess Corporation	8. Well No.
3. Address of Operator	Drawer D, Monument, New Mexico 88265	2
4. Well Location	Unit Letter <u>I</u> : <u>1980</u> Feet From The <u>South</u> Line and <u>990</u> Feet From The <u>East</u> Line	9. Pool name or Wildcat
	Section <u>16</u> Township <u>20S</u> Range <u>37E</u> NMPM <u>Lea</u> County	Eumont Yates 7RQ
10. Date Spudded	11. Date T.D. Reached	12. Date Compl. (Ready to Prod.)
		9-11-92
13. Elevations (DFA RKB, RT, GR, etc.)	14. Elev. Casinghead	
3548' DF		
15. Total Depth	16. Plug Back T.D.	17. If Multiple Compl. How Many Zones?
3842'	3654'	
18. Intervals Drilled By	Rotary Tools	Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name	20. Was Directional Survey Made	
3327' - 3524' Eumont Yates 7RQ		
21. Type Electric and Other Logs Run	22. Was Well Cored	
CBL - CCI - GR		

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB/FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
10 3/4"	32#	207'	13 3/8"	Previously Ran	150
7 5/8"	26.6#	2435'	9 7/8"	Previously Ran	400
5 1/2"	17#	3782'	6 3/4"	Previously Ran	230

LINER RECORD					TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2 7/8"	3306'	

26. Perforation record (interval, size, and number) 4" csg. gun w/2SPF at 3327', 3330', 3340', 3345', 3347', 3351', 3353', 3355', 3359', 3363', 3367', 3371', 3373', 3377', 3379', 3383', 3387', 3395', 3404', 3411'. continued over	27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.
	DEPTH INTERVAL
	AMOUNT AND KIND MATERIAL USED
	3327' - 3524' Acid w/4000 gal. 15% NEFE
	HCL acid w/126 ball sealers. Fraced w/73736 gal-cross linked 35# guar gel foamed to 50

28. PRODUCTION	quality CO2 & 250,000 12/20 Brady sand						
Date First Production	Production Method (Flowing, gas lift, pumping - Size and type pump)	Well Status (Prod. or Shut-in)					
12-2-92	Flowing	Producing					
Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl.	Gas - MCF	Water - Bbl.	Gas - Oil Ratio
12-3-92	24	3/4"		0	747	0	
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)	
90#	160#						

29. Disposition of Gas (Sold, used for fuel, vented, etc.)	Test Witnessed By
Began selling to Northern Natural on 12-2-92	

30. List Attachments

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature R. L. Wheeler, Jr. Printed Name R. L. Wheeler, Jr. Title Supv. Adm. Svc. Date 12-4-92

3A Eumont Yates 7RQ

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____	T. Simpson _____	T. Gallup _____	T. Ignacio Otzte _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Delaware Sand _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Bone Springs _____	T. Entrada _____	T. _____
T. Abo _____	T. _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
No. 2, from.....to.....
No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
perforations continued							
3420'	3422'	3423'	3429'	3433'	3439'		
3445'	3452'	3460'	3464'	3466'	3469'		
3473'	3477'	3483'	3488'	3498'	3503'		
3507'	3511'	3517'	3524'				
Total 84 Holes							