

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

| | | | |
|---|-------------------------------------|---|--|
| NOTICE OF INTENTION TO TEST CASING SHUT-OFF | <input checked="" type="checkbox"/> | NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL | |
| NOTICE OF INTENTION TO CHANGE PLANS | | NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING | |
| NOTICE OF INTENTION TO REPAIR WELL | | NOTICE OF INTENTION TO PLUG WELL | |
| NOTICE OF INTENTION TO DEEPEN WELL | | | |

Monument, New Mexico.

May 17, 1938.

OIL CONSERVATION COMMISSION,

Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

DUPLICATE


~~Amerada Petroleum Corporation~~ State Q Lease Well No. 2 in NE SE
 of Sec. 16, T. 20-S, R. 37-S, N. M. P. M., Monument Field,
 Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

This well has been drilled to TD 3788. On May 14th., 5 $\frac{1}{2}$ " OD 17# seamless casing was set at 3782' and cemented with 80 Sacks of Inceor cement and 20 sacks of Common cement. The plug was pumped to 3718' at 3 p.m. 5/14/38.. On May 16th., 138 sacks of Inceor cement was pumped between the 5 $\frac{1}{2}$ " and 7 5/8" casing thru the braden head, to shut off the upper gas.

On May 18, 1938, pump pressure of 1200# will be applied to the pipe and fittings and allowed to stand undisturbed for 30 minutes, after closing the valves. If there is no drop in pressure, the cement plug will then be drilled and the same test again applied. If there is no drop in pressure, drilling will be resumed.



MAY 20 1938

Approved _____, 19____

except as follows:

AMERADA PETROLEUM CORPORATION
Company or OperatorBy J. E. LowPosition Superintendent

Send communications regarding well to

Name J. E. LowAddress Monument, New Mexico.

OIL CONSERVATION COMMISSION,

By Guy Shepard R.M.Title Oil & Gas Inspector

Figure 1. A schematic diagram of the experimental setup. The subject is seated in a chair and views the target through a video camera. The target is a small object (e.g., a ball) that is suspended in the air. The subject's hand is positioned near the target. The video camera is positioned above the target and the subject's hand. The video camera is connected to a computer, which displays the video image of the target on a monitor. The subject's hand is positioned near the target. The video camera is positioned above the target and the subject's hand. The video camera is connected to a computer, which displays the video image of the target on a monitor.