

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION
4-NMCCC
1-File

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Getty Oil Company	8. Farm or Lease Name State I
3. Address of Operator P.O. Box 249, Hobbs, New Mexico 88240	9. Well No. 1
4. Location of Well UNIT LETTER N 330 FEET FROM THE South LINE AND 1650 FEET FROM West 16 20 S 37E THE West LINE, SECTION 16 TOWNSHIP 20 S RANGE 37E NM-PM.	10. Field and Pool, or Wildcat Monument
15. Elevation (Show whether DF, RT, GR, etc.) 3530 DF	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well is presently NIO. It is proposed to run bit and casing scraper to 3725', Set 7" 24# HWC0 cast iron bridge plug at 3710 on wireline, and dump 10' cement on top.

Perforate the Grayburg-San Andres @ 3601, 07-1/2', 16, 26, 28, 56, 61, 63, 85-1/2, and 91'. Spot 150 gallons 15% NE Acid across perforations.

Run tubing and 7" 24# RTTS. Acidize with 850 gallons 15% NE and 15 Ball Sealers. (Total acid 1,000 gal.) Swab test to recover acid.

Run tubing, pump, and rods.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original Signed By
G. L. WADE

SIGNED _____

TITLE **Area Superintendent**

DATE **January 6, 1970**

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

/bh