NEW EXICO OIL CONSERVATION COM SSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

	notice by checking below:
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL
NOTICE OF INTENTION TO DEEPEN WELL	
Monument, New	Mexico April 25, 1937
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico. Gentlemen: Following is a notice of intention to do certain work as	
Amerada Petroleum Corporation	State "Y" Well No. 1 in NE SE 4
of Sec. 17 , T. 20 , R. 37	,N. M. P. M., Monument Field
LeaCounty.	
the Halliburton Method with 600 sacks	
the Halliburton Method with 600 sacks Casing and fittings will be tested wi undisturbed for thirty minutes. If no be drilled out of the casing and the	th 1200# pump pressure and allowed to stand of drop in pressure results the cement will the same test of 1200# pump pressure will again bed for thirty minutes. If no drop in pressure
the Halliburton Method with 600 sacks Casing and fitzings will be tested wi undisturbed for thirty minutes. If no be drilled out of the casing and the applied and allowed to stand undistur	th 1200# pump pressure and allowed to stand of drop in pressure results the cement will the same test of 1200# pump pressure will again bed for thirty minutes. If no drop in pressure
Casing and fittings will be tested wi undisturbed for thirty minutes. If no be drilled out of the casing and the applied and allowed to stand undistur results the drilling will then be results.	th 1200# pump pressure and allowed to stand o drop in pressure results the cement will the same test of 1200# pump pressure will again bed for thirty minutes. If no drop in pressumed.
Casing and fittings will be tested wi undisturbed for thirty minutes. If no be drilled out of the casing and the applied and allowed to stand undistur results the drilling will then be resulted and allowed to stand undistur results the drilling will then be resulted and allowed to stand undistur results the drilling will then be resulted as a standard and allowed to stand undistur results the drilling will then be resulted as a standard and allowed to stand undistured as a standard	th 1200# pump pressure and allowed to stand of drop in pressure results the cement will to same test of 1200# pump pressure will again bed for thirty minutes. If no drop in pressumed.
Casing and fittings will be tested wi undisturbed for thirty minutes. If no be drilled out of the casing and the applied and allowed to stand undistur results the drilling will then be results.	th 1200# pump pressure and allowed to stand of drop in pressure results the cement will the same test of 1200# pump pressure will again bed for thirty minutes. If no drop in pressumed.
Casing and fittings will be tested wi undisturbed for thirty minutes. If no be drilled out of the casing and the applied and allowed to stand undistur results the drilling will then be resulted and allowed to stand undistur results the drilling will then be resulted and allowed to stand undistur results the drilling will then be resulted as a standard and allowed to stand undistur results the drilling will then be resulted as a standard and allowed to stand undistured as a standard	th 1200# pump pressure and allowed to stand of drop in pressure results the cement will the same test of 1200# pump pressure will again bed for thirty minutes. If no drop in pressumed. Amerada Fetroleum Corporation Company or Operator La La La La La Company or Operator
Casing and fitzings will be tested wi undisturbed for thirty minutes. If no be drilled out of the casing and the applied and allowed to stand undistur results the drilling will then be resulted and allowed to stand undistur results the drilling will then be resulted and allowed to stand undistur results the drilling will then be resulted as a standard	th 1200# pump pressure and allowed to stand of drop in pressure results the cement will to same test of 1200# pump pressure will again bed for thirty minutes. If no drop in pressumed. Amerada Fetroleum Corporation Company or Operator By Hunth
Casing and fitzings will be tested wi undisturbed for thirty minutes. If no be drilled out of the casing and the applied and allowed to stand undistur results the drilling will then be resulted and allowed to stand undistur results the drilling will then be resulted and allowed to stand undistur results the drilling will then be resulted as a standard	th 1200# pump pressure and allowed to stand of drop in pressure results the cement will the same test of 1200# pump pressure will again bed for thirty minutes. If no drop in pressumed. Amerada Fetroleum Corporation Company or Operator By Jacky Position Supet.
Casing and fitzings will be tested wi undisturbed for thirty minutes. If no be drilled out of the casing and the applied and allowed to stand undistur results the drilling will then be resulted and allowed to stand undistur results the drilling will then be resulted and allowed to stand undistur results the drilling will then be resulted as a standard	th 1200# pump pressure and allowed to stand of drop in pressure results the cement will to same test of 1200# pump pressure will again bed for thirty minutes. If no drop in pressumed. Amerada Petroleum Corporation Company or Operator By Laky Position Send communications ragarding well to