

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK	X	NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER) Dual Complete	X	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

May 25, 1955
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the **Theodore Andersen**

Gulf Oil Corporation
(Company or Operator) Well No. **4** in **B**
(Unit)
NW $\frac{1}{4}$ **NE** $\frac{1}{4}$ of Sec. **17**, T. **20-S**, R. **37-E**, NMPM, **Monument** Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Propose to plug back to shut off water and dually complete as an oil-gas well in the Monument Oil and the Eumont Gas Zones as follows:

1. Pull rods and tubing.
2. Run radioactivity survey.
3. Set cement retainer at 3790' and squeeze cement open hole.
4. Perforate opposite Grayburg as determined from radioactivity survey.
5. Set packer above Grayburg horizon. Swab and test. Acid treat if warranted.
6. Back off tubing at packer and pull.
7. Perforate Eumont Gas Zone as determined from radioactivity survey.
8. Set retrievable bridge plug below Eumont Zone and hookwall packer and hold down above Eumont Zone. Swab and test. Wash with mud acid and fracture treat.
9. Pull packer and bridge plug and rerun tubing and engage packer.
10. Swab in gas zone and test. Close upper circulating valve and open lower valve.
11. Produce oil thru tubing and gas thru annulus.

DC-136

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

Gulf Oil Corporation
Company or Operator
By **E. J. Taylor**
Position **Area Supt. of Prod.**
Send Communications regarding well to:
Name **Gulf Oil Corporation**
Address **Box 2167, Hobbs, N. M.**