

TRIPPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK	X	NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

March 6, 1956
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Gulf Oil Corporation (Company or Operator) Theodore Anderson Well No. 5 in F (Unit)
SE 1/4 NW 1/4 of Sec. 18, T. 20-S, R. 37-E, NMPM, Monument Pool
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

SEE ATTACHED SHEET

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

Gulf Oil Corporation
Company or Operator

By.....
Position..... Area Supt. of Prod.
Send Communications regarding well to:

Name..... Gulf Oil Corporation
Address..... Box 2167, Hobbs, New Mexico

In order to increase production it is proposed to plug back and perforate as follows:

1. Pull rods, pump and 2-3/8" tubing.
2. Run steel line measurement. Clean out with sand pump if necessary.
3. Run Gamma Ray-Neutron log and collar locator survey.
4. Run cast iron cement retainer and set in base of casing at a depth to be determined from the Gamma Ray-Neutron survey. Pressure 5-1/2" casing to 500 psi.
5. Squeeze open hole interval from 3796-3813' with 250 sacks cement. Attempt to obtain a squeeze pressure of 1000 psi.
6. If squeeze cannot be obtained, displace cement below retainer and attempt another squeeze.
7. Reverse out excess cement.
8. WOC 72 hours. Perforate interval determined from Gamma Ray-Neutron log, with 4, 1/2" jet holes per foot.
9. Run 2-3/8" tubing with packer.
10. Swab and test.