

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRII
(Other instruction
reverse side)Form Approved
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

LC-031621 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hobbs

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Eunice-Monument Gb/SA

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

18, 20-S, 37-E

12. COUNTY OR PARISH 13. STATE

Lea

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Phillips Petroleum Company

3. ADDRESS OF OPERATOR

Room 806, Phillips Building, Odessa, Texas, 79761

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

Unit L, 1980' FSL and 660' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3573 DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other) Add zone perfs

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- Propose to:
1. Pull rods, pump & tbg. Install BOP
 2. Clean out to TD 3865', with bailer
 3. Perforate bottom 15' of open hole w/1 jet shot/ft.
 4. Clean out any fill after perf
 5. Run tbg, rods and pump. Test
 6. Acidize down annulus w/2000 gals. 28% N. E. HCL with scale inhibitor.
Flush w/125 bbls fresh water
 7. Pump test.

BOP Equip.: Series 900, 3000# WP, double w/1 set pipe rams, one set blind rams; manually oper.

18. I hereby certify that the foregoing is true and correct

SIGNED

W. J. Mueller

TITLE Engineering Advisor

DATE 6-24-76

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

JUN 24 1976

BERNARD MOROZ
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side