
## NE ME O OIL CONSERVATION CC MIS. N

Santa Fe, New Mexico



## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

of the Commission. Indicate nature of report by checking below: REPORT ON BEGINNING DRILLING OPERATIONS REPORT ON REPAIRING WELL REPORT ON RESULT OF THE OR CHEMICAL TREATMENT OF WELL REPORT ON PULLING OR OTHERWISE ALTERING CASING II REPORT ON RESULT OF TEST OF CASING SHUT-OFF REPORT ON DEEPENING WELL REPORT ON RESULT OF PLUGGING OF WELL My 10, 1957, Midland, Towns. Place OIL CONSERVATION COMMISSION. Santa Fe, New Mexico. Gentlemen: Following is a report on the work done and the results obtained under the heading noted above at the... Fhillips Potroleum Company
Company or Operator \_Well No.\_\_One\_\_\_ SE/4. SR/4 \_of Sec.\_\_19\_ 20-6 ., R. **37-1**, N. M. P. M., \_\_Field, \_\_\_ Lea The dates of this work were as follows: 1957. Notice of intention to do the work was [wester] submitted on Form C-102 on 160 4 and approval of the proposed plan was free by obtained. (Cross out incorrect words.) DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED Total depth 3840 in lime. Treated pay formations from 3762 to 3840 with 5000 gallons Dowell "XX" through tubing. Started swabbing 50 minutes after treating. Swabbed 9 hours, 162 bbl. acid & oil load. Shut in at midnight. 1000f pressure on easing mext morning. Flowed 162 bbl. oil load in 34 hours. 1,100,000 gas. Next morning shut in from 7 AM to 5 PM. Opened 1 hour. Made 16 bbl. eil load & acid. Shut in to replace packer. UPLICATE Second treatment Witnessed by W. M. Spress Phillips Petroles Company Title I hereby swear or affirm that the information given above is true and correct. Subscribed and sworn to before me this. Name. 12thay of Position. <u>a</u> Notary Public Representing. Phillips Patralsus, keppany My Commission expires\_\_\_\_ Address. 4-1-37 Box #1800, Midland, Remarks: nspector/ Name Oil Conservation C

13R

HOBBS, NEW MEX

## Controlly and the control

## CARRAGO PROSES LUGAR A SUMA

The second secon where the continuous property is a second continuous factor of  $\hat{\mu}_{ij}$ 1、1964年(《宋代》、李忠公司,1974年(1975年) and the second of the second o  $t_{ij} = t_{ij} + t_{ij}$ 191 - $(r_{ij},r_{ij})$  ,  $(r_{ij},r_{ij})$  ,  $(r_{ij},r_{ij})$  ,  $(r_{ij},r_{ij})$  ,  $(r_{ij},r_{ij})$  ,  $(r_{ij},r_{ij})$ المقاولات والمعارف المواطئة المنتب ÷ X  $\mathcal{L}_{\mathcal{A}} = \{ 1, \dots, n \}$ The second of th (x,y) = (x,y) + (x,y Programme Consultation Consultation (Programme Consultation) . And the configuration  $\hat{\xi}_{ij}$  ( $\hat{\xi}_{ij}$ ) is a finite constant of  $\hat{\xi}_{ij}$  ( $\hat{\xi}_{ij}$ ) and  $\hat{\xi}_{ij}$  ( $\hat{\xi}_{ij}$ ) is a finite constant of  $\hat{\xi}_{ij}$ and the second of The second of the second of the second

Line to a second of the second of the second The state of the s

and the second section of the section of the second section of the second section of the second section of the section of the second section of the section of the

. . . .