Form C-102	
NEW MEXICO OIL CONSERV	
MISCELLANEOU	S NOTICES
Submit this notice in triplicate to the bil Conservation Commission	on or its proper agent before the work specified is CR

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is the begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

SHUT-OFF	NOTICE OF INTENTION TO <b>SHOOT OF</b> CHEMICALLY TREAT WELL	I
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL		
Midland	1, Texas June 15, 1946	
OIL CONSERVATION COMMISSION,	Place Date	
Santa Fe, New Mexico.		
Gentlemen:		
Following is a notice of intention to do certain work <b>Texas Company's State of New</b>	k as described below at the	NWŁ W
Company or Operator Lea	se	
of Sec. 19 , T. 20-8 , R. 37-E	, N. M. P. M.,	Field
Ovenvy.		
	PROPOSED PLAN OF WORK	
FOLLOW INSTRUCTIONS IN THE RU	LES AND REGULATIONS OF THE COMMISSION	
Total Depth:	3860 - Lime	
-		
" casing comented at 3620' with	h 300 sacks.	
n Test 9-95-48 well flowed 19	a so we are a stand of the second of the second s	<b></b>
on Test, 2-23-48, well flowed 13	3.11 barrels oil, no water in 24 h	ours.
OR, 19,050In an effort	to increase production of this we	ll an
OR, 19,050In an effort reduce the high GOR, the following	to increase production of this we ing work has been done: Pulled tu	ll an bing
OR, 19,050In an effort reduce the high GOR, the followi	to increase production of this we ing work has been done: Pulled tu	ll an bing
OR, 19,050In an effort reduce the high GOR, the followi	to increase production of this we ing work has been done: Pulled tu	ll an bing
OR, 19,050In an effort reduce the high GOR, the following and ran Caliper Survey to Total Can Lans-Wells Survey, 2-1/2" to b' tubing perforation at 3828'.	to increase production of this we ing work has been done: Pulled tu Depth. Ran Spinner Survey 3812-3 tubing was run with packer at 3825 Well was swabbed 15 hours, 75 ba	ll an bing B18'. ', rrels
FOR, 19,050In an effort reduce the high GOR, the following and ran Caliper Survey to Total an Lane-Wells Survey, 2-1/2" to tubing perforation at 3828'. bil. No test on BS&W. We now d	to increase production of this we ing work has been done: Pulled tu	ll an bing B18'. ', rrels
OR, 19,050In an effort reduce the high GOR, the following and ran Caliper Survey to Total an Lane-Wells Survey. 2-1/2" to tubing perforation at 3828'. 11. No test on BStW. We now d	to increase production of this we ing work has been done: Pulled tu Depth. Ran Spinner Survey 3812-3 tubing was run with packer at 3825 Well was swabbed 15 hours, 75 ba	ll an bing 818'. ', rrels
OR, 19,050In an effort educe the high GOR, the followind ran Caliper Survey to Total an Lane-Wells Survey. 2-1/2" to tubing perforation at 3828'. il. No test on BStW. We now d	to increase production of this we ing work has been done: Pulled tu Depth. Ran Spinner Survey 3812-3 tubing was run with packer at 3825 Well was swabbed 15 hours, 75 ba	ll an bing 818'. ', rrele
OR, 19,050In an effort educe the high GOR, the followind ran Caliper Survey to Total an Lane-Wells Survey. 2-1/2" to tubing perforation at 3828'. il. No test on BS&W. We now d	to increase production of this we ing work has been done: Pulled tu Depth. Ran Spinner Survey 3812-3 tubing was run with packer at 3825 Well was swabbed 15 hours, 75 ba	ll ar bing 818'. ', rrele
OR, 19,050In an effort educe the high GOR, the followind ran Caliper Survey to Total an Lane-Wells Survey. 2-1/2" t tubing perforation at 3828'. 11. No test on BStW. We now d	to increase production of this we ing work has been done: Pulled tu Depth. Ran Spinner Survey 3812-3 tubing was run with packer at 3825 Well was swabbed 15 hours, 75 ba	ll an bing 818'. ', rrele
OR, 19,050In an effort educe the high GOR, the followind ran Caliper Survey to Total an Lane-Wells Survey. 2-1/2" to tubing perforation at 3828'. 11. No test on BS&W. We now d	to increase production of this we ing work has been done: Pulled tu Depth. Ran Spinner Survey 3812-3 tubing was run with packer at 3825 Well was swabbed 15 hours, 75 ba	ll an bing 818'. ', rrels
Approved 19,050In an effort educe the high GOR, the following and ran Caliper Survey to Total an Lane-Wells Survey, 2-1/2" to tubing perforation at 3628'. il. No test on BS&W. We now do Dowell) acid 3826-3860'.	to increase production of this we ing work has been done: Pulled tu Depth. Ran Spinner Survey 3812-3 tubing was run with packer at 3825 Well was swabbed 15 hours, 75 ba	ll an bing 818'. ', rrels
Approved	to increase production of this we ing work has been done: Pulled tu Depth. Ran Spinner Survey 3812-3 tubing was run with packer at 3825 Well was swabbed 15 hours, 75 bas lesire to acidize with 4000 gallons	ll an bing 818'. ', rrels
Approved	to increase production of this we ing work has been done: Pulled tu Depth. Han Spinner Survey 3812-3 tubing was run with packer at 3825 Well was swabbed 15 hours, 75 bas lesire to acidize with 4000 gallons The Texas Company Company or Operator	ll an bing B18'. ', rrels
Approved	to increase production of this we ing work has been done: Pulled tu Depth. Ran Spinner Survey 3812-3 tubing was run with packer at 3825 Well was swabbed 15 hours, 75 basis tesire to acidize with 4000 gallons The Texas Company	ll an bing B18'. ', rrels
Approved	to increase production of this we Ing work has been done: Pulled tu Depth. Ren Spinner Survey 3812-3 tubing was run with packer at 3825 Well was swabbed 15 hours, 73 bas lesire to acidize with 4000 gallons Company or Operator By Company or Operator By Dist. Supt.	ll an bing SlS'. rrels
Approved 19,050.	to increase production of this we ing work has been done: Pulled tu Depth. Hen Spinner Survey 3812-3 tubing was run with packer at 3825 Well was swabbed 15 hours, 75 bas lesire to acidize with 4000 gallons lesire to acidize with 4000 gallons By Company or Operator By Company or Operator	ll an bing Sl8'. rrels
Approved	to increase production of this we Ing work has been done: Pulled tu Depth. Ren Spinner Survey 3812-3 tubing was run with packer at 3825 Well was swabbed 15 hours, 73 bas lesire to acidize with 4000 gallons Company or Operator By Company or Operator By Dist. Supt.	ll and bing Sl8'. rrels
ApprovedJUN 2 11948, 19	to increase production of this we Ing work has been done: Pulled tu Depth. Ran Spinner Survey 3812-3 tubing was run with packer at 3825 Well was swabbed 15 hours, 73 bas lesire to acidize with 4000 gallons lesire to acidize with 4000 gallons By Company or Operator By Company or Operato	ll and bing Bl8'. ', rrels B
ApprovedJUN 2 11948, 19	to increase production of this we Ing work has been done: Pulled tu Depth. Ren Spinner Survey 3812-3 tubing was run with packer at 3825 Well was swabbed 15 hours, 73 bas lesire to acidize with 4000 gallon: Lesire to acidize with 4000 gallon: By Company or Operator By Company or Operator	ll an bing BlS'. rrels
ApprovedJUN 2 11948, 19	to increase production of this we Ing work has been done: Pulled tu Depth. Ran Spinner Survey 3812-3 tubing was run with packer at 3825 Well was swabbed 15 hours, 75 basis tesire to acidize with 4000 gallons Hesire to acidize with 4000 gallons By Company or Operator By Company or Operator Box 1270, Midland,	ll ar bing Bl8'. rrela

.

\* . . •

and a second second

· · · · · ·

Play qualitates