

DUPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
JUL 7 1948
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	X	REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

July 6, 1948

Midland, Texas

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
The Texas Company's State of New Mexico "G" (Univ) Well No. **6** in the _____

Company or Operator **NW 1 NE 1** of Sec. **19**, T. **20-S**, R. **37-E**, N. M. P. M.,
Monument Field, **See below** County.

The dates of this work were as follows:

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on **June 15** 19 **48**
and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Total Depth: 3860' - Line

In an effort to increase production and reduce high GOR, Well was acidized 6-15-48. Packer was set at 3825'. Zone Acidized 3826-3860' with 4000 gallons Dowell acid. Perforated 2-1/2" tubing at 3768' with 1/4" hole. Set Otis Side Door Choke (2/64" choke) at 3768'. Installed intermitter and on test 7-5-48 well flowed 19.32 barrels oil in 24 hours, 3.5% BS&W. GOR 7410'.

Witnessed by _____ Name _____ Company _____ Title _____

Subscribed and sworn before me this _____

6th day of **July**, 19 **48**

Mary L. Cochran
Notary Public

My commission expires **June 1, 1949**

I hereby swear or affirm that the information given above is true and correct.

Name *W. R. ...*

Position **Dist. Supt.**

Representing **The Texas Company**
Company or Operator

Address **Box 1270, Midland, Texas**

Remarks:

APPROVED

Date **JUL 7 1948**

Roy Guhraugh
Name
OIL & GAS INSPECTOR
Title

1800/1801