NEV MEXICO OIL CONSERVATION CC **IISSION**

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate	nature	of	notice	by	checking	below:
----------	--------	----	--------	----	----------	--------

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	x	NOTICE OF INT	ENTION TO	O SHOOT WELL	OR	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PU OTHERWISE ALTER CASING		O PULL ASING	LL OR	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INT	ENTION TO	o PLUG V	VELL	
NOTICE OF INTENTION TO DEEPEN WELL	- !					
	Win	k, Texas, M	ay 9,	1937		
	F	Place			Date	
OIL CONSERVATION COMMISSION,						
Santa Fe, New Mexico.						
Gentlemen:			יאדי	TEXAS	COMPANY	
Following is a notice of intention to do certain work State		Land		8	NE-1/4	
Company or Operator 20 S B 37 E	N	Lease	vell No.—. Monu		inFie	
or sec, r, r	,,1\	. W. FW.,				
LeaCounty.						
	9 - 5/8	9" OD 40# 8t	h d se a	mless	casing	
T. D. 1166' Anhydrite.	9-5/8 s Tri	on 40# 8t nity common	hd sea Gemen	mless t. Co	casing ompleted	
T. D. 1166' Anhydrite. Set and cemented 1140' of (37 Jts) at 1157' with 600 sacks cementing at 8:00PM 5-8-37. Anticipate drilling plug at 8:00PM 5-11-37.	9-5/8 s Tri	or on 40# 8t; nity common esting casing	hd sea cemen g by p	mless t. Coressur	casing ompleted re method	
T. D. 1166' Anhydrite. Set and cemented 1140' of 3 (37 Jts) at 1157' with 600 sacks cementing at 8:00PM 5-8-37. Anticipate drilling plug as	9-5/8 s Tri	or OD 40# 8t. nity common sting casing	hd sea cemen g by p	mless t. Coressur	casing ompleted re method	
T. D. 1166' Anhydrite. Set and cemented 1140' of (37 Jts) at 1157' with 600 sacks cementing at 8:00PM 5-8-37. Anticipate drilling plug at 8:00PM 5-11-37.	9-5/8 s Tri	or OD 40# 8t. nity common sting casing	hd sea cemen g by p	mless t. Coressur	casing ompleted re method	
T. D. 1166' Anhydrite. Set and cemented 1140' of (37 Jts) at 1157' with 600 sacks cementing at 8:00PM 5-8-37. Anticipate drilling plug at 8:00PM 5-11-37. Approved	9-5/8 s Tri	or on 40# 8th nity common sting casing	hd sea cemen g by p	ressur	casing ompleted re method	
T. D. 1166' Anhydrite. Set and cemented 1140' of (37 Jts) at 1157' with 600 sacks cementing at 8:00PM 5-8-37. Anticipate drilling plug at 8:00PM 5-11-37. Approved	9-5/8 s Tri nd te	osition Dis	hd searcement g by post TEXAS	comp.	casing ompleted re method	
T. D. 1166' Anhydrite. Set and cemented 1140' of (37 Jts) at 1157' with 600 sacks cementing at 8:00PM 5-8-37. Anticipate drilling plug at 8:00PM 5-11-37. Approved	9-5/8 s Tri nd te	THE y Osition Send comm	hd searcement g by post TEXAS	comp r Operator	casing ompleted re method ANY Intendent in tendent in	