cc: VDA JTR

## "NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOTES OFFICE OCC. Juny 1

| oleted. It should be signed and filed as a  | report on Beginning Drilling nt operations, even though the   | Operations, Results o  | on, within 10 days after the work speci<br>f test of casing shift-off, result of plugs<br>d by an agent of the Commission. See | ing of well: |
|---|---|--|--|--------------|
|   | Indicate Nature of Re   | eport by Checking B  | elow   |              |
| REPORT ON BEGINNING OPERATIONS  | REPORT ON RES<br>OF CASING SHU  |  | REPORT ON<br>REPAIRING WELL  | x            |
| EPORT ON RESULT<br>F PLUGGING WELL  | REPORT ON REC   | OMPLETION  | REPORT ON<br>(Other)   |              |
|   | May 2   | 29, 1954   | Hobbs, New Mexice  |              |
| Following is a report on the work   | ,   |  |  |              |
| Sinclair Oil & Gas Company (Company or Operator)  |   | W. C. Reach  |  |              |
| Mebile Incorporated   |   | , Well No. <b>1</b>  | in the 14 14 of Sec  | 21           |
| (Contractor   |   | Pool,  | T.es   |              |
|   |   |  | 200  | County.      |
| he Dates of this work were as folows:   | May 18, 1954  |  |  |              |
| otice of intention to do the work (was)   | (value) submitted on Form   | n C-102 on   | May 6, 1954<br>(Cross out incorrect words)   | , 19 ,       |
| nd approval of the proposed plan (was)  | (was not) obtained.   |  |  |              |
|   | TIP ACCOUNT OF WORK   |  | TTS ORTAINED   |              |
|   |   | DONE AND RESU  |  |              |
| 3836 - Cleaned out from<br>Plugged back wit<br>petrofraced with   | 3823 to 3836, plug<br>h Hydromite to 3798<br>6,000 gallens of o<br>5th, 56 barrels of<br>5th, 78 "              | ged back with<br>. Acidized wi<br>iland 6,000# c                         |  | asion ac     |
| 38% - Cleaned out from<br>Plugged back with<br>petrofraced with<br>MTD 3790 - swabbed May 2<br>May 2                    | 3823 to 3836, plugh Hydromite to 3798 6,000 gailens of ofth, 56 barrels of 6th, 78 "7th, 72 "                   | ged back with<br>. Acidized wi<br>iland 6,000# c                         | cement to 3797.  ith 750 gallens of lew ter  of sand from 3712 to 3790.  |              |
| 38% - Cleaned out from Plugged back with petrofraced with TD 3790 - swabbed May 2 May 2 May 2                           | 3823 to 3836, plug<br>h Hydromite to 3796<br>6,000 gailens of o<br>5th, 56 barrels of<br>5th, 78 "<br>7th, 72 " | ged back with Acidized will and 6,000# coil. ""  Oil & Gas Com (Company) | apany  Asst. foremar   |              |
| 38% - Cleaned out from Plugged back with petrofraced with TD 3790 - swabbed May 2 May 2 May 2 May 2  Ira L. Wag  (Name) | 3823 to 3836, plug<br>h Hydromite to 3796<br>6,000 gailens of o<br>5th, 56 barrels of<br>5th, 78 "<br>7th, 72 " | ged back with Acidized will and 6,000# coil.                             | apany  Asst. foremar   | <b>.</b>     |

Address Bex 1927

(Date)

Hobbs, New Mexico