

Submit 3 Copies To Appropriate District Office

District I
1625 N. French Dr., Hobbs, NM 88240

District II
811 South First, Artesia, NM 88210

District III
1000 Rio Brazos Rd., Aztec, NM 87410

District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐	WELL API NO. 30-025-06207
2. Name of Operator Chevron USA, Inc.	5. Indicate Type of Lease STATE ☒ FEE ☐
3. Address of Operator 15 Smith Rd., Midland, Texas 79705	6. State Oil & Gas Lease No.
4. Well Location Unit Letter L : 1650 feet from the South line and 330 feet from the West line Section 32 Township 20S Range 37E NMPM Lea County	7. Lease Name or Unit Agreement Name: Eunice Monument South Unit
10. Elevation (Show whether DR, RKB, RT, GR, etc.)	8. Well No. 157
	9. Pool name or Wildcat Eunice Monument Grayburg SA

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒ TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐ OTHER: ☐	SUBSEQUENT REPORT OF: REMEDIAL WORK ☐ ALTERING CASING ☐ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐ CASING TEST AND CEMENT JOB ☐ OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

1. Notify OCD 24 hrs prior to MI & RU.
2. Set 7" CIBP @ 3600', (Grayburg-San Andres) Spot 40 Sx plug 3600'-3400' (Queen) WOC Tag.
3. Displace hole w/MLF, 9.5# Brine w/25# Gel P/BBL.
4. Perf 4 holes @ 2600', sqz 75 Sx plug 2600'-2400' (B-Salt) WOC Tag.
5. Cut 7" Csg @ 1275', L/D Csg.
6. Spot 100 Sx plug 1325'-1100', (9 5/8" Shoe, T-Salt) WOC Tag.
7. Spot 75 Sx plug 320'-150' (12 1/2" Shoe) WOC Tag.
8. 10 Sx Surf, Install dry hole marker.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE G.R. Bledsoe

TITLE HES Specialist

DATE 5/29/2002

Type or print name G.R. Bledsoe

(This space for State use)

Telephone No. 915.687.7153

APPROVED BY

Conditions of approval, if any:

ORIGINAL SIGNED BY
GARY W. WINK

FIELD REPRESENTATIVE II/STAFF MANAGER

DATE 29 2002

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.

PLUGGING & ABANDONMENT WORKSHEET

OPERATOR CHE ON USA INC
 LEASE NAME EUNICE MONUMENT SOUTH UNIT
 WELL # 157

SECT 32 TWN 20-S RNG 37-E
 FROM 1650 NISL 330 EWL
 TD 3861 FORMATION @ TD SAN ANDRES
 PBTD FORMATION @ PBTD GRAYBURG

	SIZE	SET @	TOC	TOC DETERMINED BY
SURFACE	12 1/2	264	SURF	Circ
INTMED 1	9 5/8	1215	SURF	Circ
INTMED 2				
PROD	7"	3720	2798	CALC

	SIZE	TOP	BOT	TOC	DETERMINED BY
LINER 1					
LINER 2					

	CUT & PULL	TOP - BOTTOM
INTMED 1		PERFS
INTMED 2		3654 - 3780
PROD	1275	OPENHOLE

*REQUIRED PLUGS DISTRICT

	PLUG	TYPE PLUG	SACKS CEMENT	DEPTH
RUSTLER (ANHYD)	1	CIBP		3600
YATES	2	QUEEN	400	3600
QUEEN	3	B-SALT	75	2600
GRAYBURG	4	9 5/8 SHOE	100	1325
SAN ANDRES	5	12 1/2 SHOE	75	320
CAPTAN REEF	6	SURFACE	10	10
DELAWARE				
BELL CANYON				
CHERRY CANYON				
BRUSHY CANYON				
BONE SPRING				
GLORIETA				
BLINBRY				
TUBB				
DRINKARD				
ABO				
WC				
PENN				
STRAWN				
ATOKA				
MORROW				
MISS				
DEVONIAN				

MLF

12 1/2

@ 264

TOC SURF

MLF

9 5/8

@ 1215

TOC SURF

MLF

MLF

7"

@ 3720

TOC 2798

TD 3861