					COFY TO O.	Çira har		MF	CEIVGCA		
			NI	EN	COMinSION	V KB					
					Santa Fe, New Mexico				SEP 14 1953		
	N	JOTI	CE C	אד דו	NTENTION TO DRILL <del>OR RECO</del>						
	_							5 T			
begins. If Submit thi	changes in t	he prop QUINT	osed plar	are co	e of the Oil Conservation nsidered advisable, a cop le copy will be returned	ov of this notice	e showing such cl	hanges will be	returned to the sender.		
tions of the	e Commission		i <b>e</b> w M	avir	0		Sentoph		ECE! VEIU		
			(Place)			Las Cru		(Date)	SEP14 1000		
	SERVATIC		IMISSIC	N							
	E, NEW MI	EXICO				03173	56/2-1	2 · · ·	S. GEOLOGICA: SIRDERA 1008S, NELAN (DRV		
Gentlemen: You are hereby notified that it is our intention to commence the (Drilling) (Recompletion) of a well to be known as											
100 6	are nereby n		Mat 11 13	KORA	is R. Anthe IL	, OIL OP	ERATOR				
	Stano	lind-	-Fede	ral	(Company o	· · · ·	1	<b>.</b>	E		
•••••			(Lease)		••••••••••••••••••••••••••••••••••••••						
located	660		t from t	he	West				<b>Q</b> feet from the		
	NO				line of Section		20 S	_	•		
(GIVE LO	OCATION I	FROM S	SECTION	I LINE			م تتما		County		
[		i		1	If State Land the Oil and If patented land the own				-		
D	С	в	А		Address		<u> </u>				
					We propose to drill well surface to		uipment as fellow	Rotar	y from		
0	F	G	Н		The status of allowing h	AD	neoved an	fon fill	e-in-your		
					The status of plugging b						
L	к	J	I		Drilling Contractor	Makin	Drilling	Company	,		
						Hobbs	Alew Mex	lco			
М	N	0	4/		We intend to complete t	his well in the	Queen				
Ĺ					formation at an approxi	and the second se	3620		feet.		
					CASING P	S.					
We p	ropose to use	the foll	owing sta	ings of	Casing and to cement the	en as indicated	: 		<u> </u>		
Size	of Hole	5	size of Cas	ńg 👘	Weight per Foot	New or Second	Hand	Depth	Sacks Cement		

Size of Hole	Size of Casing	Weight per Foot	New or Second Hand	Depth	Sacks Cement
11.	8-5/8	32#	S. H.	220*	125
8-3/4*	5-1/2"	15.5#	S. H.	3500*	250 +

If changes in the above plans become advisable we will notify you immediately.

ADDITIONAL INFORMATION (If recompletion give full details of proposed plan of work.)

## A two stage cementing tool will be run at 1250\* from the wurface; 125 sacks cement will be pumped around the shoe and 125 sacks used through the two stage tool.

Approved 19	Sincerely yours,			
Except as follows:	MORRIS R. ANTWEIL			
the for the first	By			
1 tailA	Agent			
OIL CONSERVATION COMMISSION	Send Communications regarding well to			
_	Name J. W. Adams			
By	Address Box 1058			
Title	Hobbs, New Mexico			